



Maxx® (Model 89086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

Bearings & Bushings

- 5106A Ball bearing, black rubber sealed (15x24x5mm) (2)
- 5107A Ball Bearing, black rubber sealed (17x26x5) (2)
- 5099A Ball bearing, black rubber sealed (6x16x5mm) (2)
- 2728 Ball bearings (5x8x2.5mm) (2)
- 5119A Ball bearings, black rubber sealed (10x15x4mm) (2)
- 5120A Ball bearings, black rubber sealed (12x18x4mm) (2)
- 5101A Ball bearings, black rubber sealed (12x21x5mm) (2)
- 5098A Ball bearings, black rubber sealed (17x23x4mm) (2)
- 5180A Ball bearings, black rubber sealed (6x13x5mm) (2)
- 5118A Ball bearings, black rubber sealed (8x16x5mm) (2)
- 5101 Ball bearings, blue rubber sealed (12x21x5mm) (2)
- 7020 Ball bearings, blue rubber sealed (8x12x3.5mm) (2)

Body & Accessories

- 8915 Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (9)
- 8910 Body reinforcement set, Maxx® (fits #8911 body)
- 8913R Body support, rear/ 3x10mm CS (4) (fits 8918 series Maxx® bodies for 352mm wheelbase)
- 8918 Body, Maxx® (clear, requires painting)/ window masks/ decal sheet (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918A Body, Maxx®, blue (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918G Body, Maxx®, green (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918T Body, Maxx®, orange (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918X Body, Maxx®, ProGraphix® (graphics are printed, requires paint & final color application)/ decal sheet (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918R Body, Maxx®, red (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8931 Body, Maxx®, Rock n' Roll (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8918P Body, Maxx®, yellow (painted, decals applied) (fits Maxx® with extended chassis (352mm wheelbase))**
- 8917 Skid plate, roof (body) (black)/ 3x10mm CS (4)
- 8917X Skid plate, roof (body) (blue)/ 3x10mm CS (4)**
- 8917G Skid plate, roof (body) (green)/ 3x10mm CS (4)**
- 8917T Skid plate, roof (body) (orange)/ 3x10mm CS (4)**
- 8917R Skid plate, roof (body) (red)/ 3x10mm CS (4)**
- 8912X Tailgate protector, blue/ 3x10mm flat-head screw (3)**
- 8912G Tailgate protector, green/ 3x10mm flat-head screw (3)**
- 8912T Tailgate protector, orange/ 3x10mm flat-head screw (3)**
- 8912R Tailgate protector, red/ 3x10mm flat-head screw (3)**
- 8912 Tailgate protector/ 3x10mm flat-head screw (3)

Bumpers & Skidplates

- 8933 Bumper mount, front
- 8934 Bumper mount, rear
- 8935 Bumper, front
- 8935X Bumper, front (for use with #8990 LED light kit)**
- 8936 Bumper, rear
- 8936X Bumper, rear (for use with #8990 LED light kit)**
- 8945 Skidplate, center/ 4x20 CCS (4)/ 3x10 CS (4)
- 8944 Skidplate, front (1), rear (1)

Chassis & Attachments

- 8919R Battery hold-down/ mounts (front & rear)/ battery compartment spacers/ foam pads (fits Maxx® with extended chassis (352mm wheelbase))
- 8915 Body mounts, front & rear/ 3x12mm BCS (1)/ 3x12mm shoulder screw (2)/ 3x10mm flat-head machine screw (9)
- 8924 Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 2.5x10 CS (2)/ 3x10 CCS (3)
- 8933 Bumper mount, front
- 8934 Bumper mount, rear
- 8935 Bumper, front
- 8936 Bumper, rear
- 8922R Chassis (fits Maxx® with extended chassis (352mm wheelbase))
- 8921 Chassis brace, front
- 8987 Covers, gear (2)
- 8923 Nerf bars, chassis (2)
- 8925 Seal kit, receiver box (includes o-ring, seal, and silicone grease)
- 8938 Shock tower, front (left & right halves)
- 8939 Shock tower, rear (left & right halves)

- 8945R Skidplate, center/ 4x20 CCS (4)/ 3x10 CS (4) (fits Maxx® with extended chassis (352mm wheelbase))
- 8944 Skidplate, front (1), rear (1)
- 7717R Spacer, battery compartment (1) (for use with #2872X 3-cell 5000mAh LiPo battery in Maxx®)**
- 7799 Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels)**
- 8976 Wheelie Bar
- 8976X Wheelie bar, blue**
- 8976G Wheelie bar, green**
- 8976T Wheelie bar, orange**
- 8976R Wheelie bar, red**
- 8976A Wheelie bar, white**
- 7775 Wheels, wheelie bar (2)/ axles, wheelie bar (2)/ 10x15x4 plastic bushings (4) (for #7776, 8976, or 9576 wheelie bar)
- 7775X Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)**
- 7775A Wheels, wheelie bar, 6061-T6 aluminum (dark titanium-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)**
- 7775G Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)**
- 7775T Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)**
- 7775R Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearings (4)**

Cush Drive Components

- 6465 Cush drive key/ pin/ elastomer damper
- 7793X Housing, cush drive (front & rear halves)
- 6447 Spur Gear, 46-tooth (1.0 metric pitch)**
- 6442 Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)**
- 6448 Spur Gear, 50-tooth (1.0 metric pitch)
- 6443 Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)**
- 6449 Spur Gear, 54-tooth (1.0 metric pitch)
- 6444 Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)**
- 6449X Spur gear, 54-tooth, steel (1.0 metric pitch)**

Differential Components

- 8681X Carrier, differential (aluminum)/ x-ring gaskets (2)/ ring gear gasket/ spacers (4)/ 12.2x18x0.5 MW**
- 8981 Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW
- 8991 Differential, front, complete (fits Maxx®)**
- 8992 Differential, rear, complete (fits Maxx®)**
- 8980 Differential kit, center (complete)**
- 5136X Differential oil kit (1 each: 10K, 30K, 50K weights)**
- 8949 Differential output yoke assembly, front or rear (assembled with external-splined half shaft)
- 8982 Gear set, differential (output gears (2)/ spider gears (4)/ spider gear shaft (2)/ output shaft (2)/ 2.5x13.8 pin (2))
- 8682 Gear set, differential (spider gears (4), spider gear shaft (2))**
- 8988 Gear, center differential, 44-tooth
- 8688 Gear, center differential, 44-tooth (fits #8980 center differential)**
- 5041 Grease, premium high performance (20cc)
- 8985 Input gear, transmission, 22-tooth/ 2.5x12mm pin
- 8986 Input shaft, transmission
- 5130 Oil, differential (100K wt) (0.7 oz (20cc))**
- 5135 Oil, differential (10K wt) (1.7 oz (50cc))**
- 5040 Oil, differential (20M wt) (standard)
- 5136 Oil, differential (30K wt) (1.7 oz (50cc))**
- 5137 Oil, differential (50K wt) (1.7 oz (50cc))
- 8989 Output gear, center differential, hardened steel (2)
- 8684 Output gear, center differential, hardened steel (2)**
- 8978 Ring gear, differential/ pinion gear, differential (front)
- 8977 Ring gear, differential/ pinion gear, differential (rear)
- 8953 Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft)

Driveline Components

- 8952X Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)**
- 8952G Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)**
- 8952 Carriers, stub axle (left & right)
- 8952A Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)**

Page 2 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89086-4) Parts List

| | | | |
|-------|---|-------|--|
| 8952R | Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2) | 8937 | Steering blocks, left & right |
| 8951 | Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X steel CV driveshafts) | 8999 | Suspension arms, lower, black (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8954 | Drive hub, front (1)/ 3x10 screw pin (1) | 8999X | Suspension arms, lower, blue (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996 | Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) (for use with #8995 WideMaxx™ suspension kit) | 8999G | Suspension arms, lower, green (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8955R | Driveshaft, center, aluminum (fits Maxx® with extended chassis (352mm wheelbase)) | 8999T | Suspension arms, lower, orange (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996R | Driveshaft, steel constant velocity (shaft only, 109.5mm) (1) (replacement shaft for #8996X) | 8999R | Suspension arms, lower, red (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996A | Driveshaft, steel constant-velocity (shaft only, 109.5mm) (4) (for conversion of #8950X driveshafts to WideMaxx® suspension) | 8998 | Suspension arms, upper, black (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996X | Driveshafts, steel constant-velocity (assembled), front or rear (4) (for use with #8995 WideMaxx® suspension kit) (requires #8654 series 17mm splined wheel hubs and #7758 series 17mm nuts for a complete set) | 8998X | Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8993 | Half shaft set, left or right (plastic parts only) (internal splined half shaft/ external splined half shaft) (4 assemblies) (for use with #8995 WideMaxx™ suspension kit) | 8998G | Suspension arms, upper, green (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8993A | Half shafts, outer (extended, front or rear) (4)/ e-clips (8) (for use with #8995 WideMaxx™ suspension kit) | 8998T | Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8447A | Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) | 8998R | Suspension arms, upper, red (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8447X | Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4) | 7743 | Suspension pin retainer (4) |
| 8447G | Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) | 8940X | Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4) retainers (8) |
| 8447R | Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) | 8942 | Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) |
| 8447 | Nuts, 5mm flanged nylon locking (steel, black serrated) (8) | 8941 | Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel) |
| 5040 | Oil, differential (20M wt) (standard) | 8940 | Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2) |
| 8953 | Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) | 8997X | Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8956 | Wheel hubs, hex (2)/ 2.5x14 pins (2) | 8997G | Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8956X | Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) | 8997A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8956G | Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4) | 8997R | Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8956T | Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) | | |
| 8956R | Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) | | |
| 8654 | Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | | |
| 8654G | Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | | |
| 8654A | Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) | | |
| 8654R | Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | | |
| 8957 | Wheel washers (4) | | |
| 8957X | Wheel washers, blue (4) | | |
| 8957G | Wheel washers, green (4) | | |
| 8957T | Wheel washers, orange (4) | | |
| 8957R | Wheel washers, red (4) | | |

Front Suspension & Steering

| | |
|-------|---|
| 8926 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) |
| 8920 | Bulkhead, front (upper and lower) |
| 8932X | Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) |
| 8932G | Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) |
| 8932A | Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) |
| 8932R | Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) |
| 8932 | Caster blocks (c-hubs), left & right |
| 8916 | Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) |
| 8958 | Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) |
| 8947 | Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) |
| 8938 | Shock tower, front (left & right halves) |
| 8946 | Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) |
| 8937X | Steering blocks, 6061-T6 aluminum (blue-anodized), left & right |
| 8937G | Steering blocks, 6061-T6 aluminum (green-anodized), left & right |
| 8937A | Steering blocks, 6061-T6 aluminum (orange-anodized), left & right |
| 8937R | Steering blocks, 6061-T6 aluminum (red-anodized), left & right |

Hardware

| | |
|-------|---|
| 1552 | 3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1) |
| 3642 | Attachment screws, shock (3x12mm shoulder screws) (6) |
| 4859 | CS 3x10 flathead (hex drive) |
| 2584 | Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX® 2.5, 2.5R, 3.3) |
| 8447A | Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4) |
| 8447X | Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4) |
| 8447G | Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) |
| 8447R | Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) |
| 8447 | Nuts, 5mm flanged nylon locking (steel, black serrated) (8) |
| 5147X | Nuts, 5mm flanged nylon locking (steel, serrated) (8) |
| 3236 | Screws, 2.5x12mm cap-head machine (6) |
| 2577 | Screws, 3x10mm button-head machine (hex drive) (6) |
| 2587 | Screws, 3x10mm caphead machine (6) (no washer) |
| 2551 | Screws, 3x10mm countersunk machine (6) (hex drive) |
| 2578 | Screws, 3x12mm button-head machine (hex drive) (6) |
| 2579 | Screws, 3x15mm button-head machine (hex drive) (6) |
| 2553 | Screws, 3x15mm countersunk machine (6) (hex drive) |
| 3646 | Screws, 3x15mm flat-head machine (hex drive) (6) |
| 2583 | Screws, 3x18 button-head machine (hex drive) (6) |
| 2581 | Screws, 3x25mm button-head machine (hex drive) (6) |
| 2582 | Screws, 3x30mm button-head machine (hex drive) (6) |
| 2550 | Screws, 3x8mm countersunk machine (6) (hex drive) |
| 3936 | Screws, 4x10mm button-head machine (hex drive) (6) |
| 2535 | Screws, 4x10mm countersunk machine (hex drive) (6) |
| 3937 | Screws, 4x12mm button-head machine (hex drive) (6) |
| 3938 | Screws, 4x14mm button-head machine (hex drive) (6) |
| 3933 | Screws, 4x16mm button-head machine (hex drive) (6) |
| 2589 | Screws, 4x20mm button-head machine (hex drive) (6) |
| 2596 | Screws, 4x25mm button-head machine (hex drive) (6) |
| 2595 | Screws, 4x35mm button-head machine (hex drive) (6) |
| 8940X | Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) |

Page 3 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89086-4) Parts List

- 8942 Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)
- 8943 Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)

LED Lights

- 6590 High-Voltage Power Amplifier
- 7884 LED light bar, front (high-voltage) (40 white LEDs (double row), 82mm wide) (fits Maxx®, X-Maxx®, or XRT™)
- 7883 LED light bar, rear, red (with white reverse light) (high-voltage) (24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits Maxx®, X-Maxx®, or XRT™)
- 8990 LED light kit, MMT01 complete (includes #6590 high-voltage power amplifier)

Motors & Electronics

- 7749 Adapter, standard servo (adapts standard servo to fit in X-Maxx®) Adapter, standard servo (adapts standard servo to fit in Maxx®, X-Maxx®, or XRT™)
- 3463 Cooling fan kit (with shroud), Velineon® 540XL motor
- 3475 Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)
- 8987 Covers, gear (2)
- 2092 Gear set (for 2090 servo)
- 3462 Heat sink, Velineon® 540XL motor
- 8960 Motor mounts (front and rear)/ 4x10 BCS with split and flat washers (1)/ pin (1)
- 8960X Motor mounts (front and rear)/ 4x10 BCS with split and flat washers (1)/ pin (1) (for installation of #3481 motor into Maxx®)
- 3461 Motor, Velineon® 540XL, 2400Kv 70mm, brushless (assembled with 6.5mm gold-plated bullet connectors) (for Maxx®/Hoss®) (not for use in marine models)
- 3464 Mount, motor cooling fan (fits #3458 heat sink)
- 3352R Rebuild kit, Velineon® 3500 (includes plastic endbell, 5x11x4mm ball bearings (2), 2.5x5mm BCS (with threadlock) (4), rear bushing)
- 2091 Servo case/ gaskets (for 2090 waterproof servo)
- 8947X Servo horn, steel
- 8947 Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
- 2090 Servo, digital high-torque (ball bearing), waterproof
- 2085 Servo, digital high-torque (ball bearing), waterproof
- 2085X Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
- 3465 Velineon VXL-4s High Output Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)

Radio System, Batteries & Chargers

- 2872X 5000mah 11.1v 3-Cell 25C LiPo Battery
- 2889X 5000mah 14.8v 4-Cell 25C LiPo Battery (long)
- 2857X 6400mah 11.1v 3-Cell 25C LiPo Battery
- 2890X 6700mah 14.8v 4-Cell 25C LiPo Battery
- 2914 Battery, Power Cell AA Alkaline (4)
- 2938X Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD® batteries to separate balance ports)
- 1926 Antenna caps, vinyl (2)/ antenna spool
- 1726 Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
- 1726A Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1)
- 2943 Battery charge indicators, green (4), grey (4), blue (4)
- 6548 Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter)
- 2996X Battery/charger completer pack (includes #2971 iD charger (1), #2889X 5000mAh 14.8V 4-cell 25C LiPo iD® battery (1))
- 2990 Battery/charger completer pack (includes #2972 Dual iD charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery (2))
- 2998 Battery/charger completer pack (includes #2981 iD charger (1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (1))
- 2972 Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification
- 2973 Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto Battery Identification
- 2970 Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery Identification
- 2971 Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification
- 2981 Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto Battery Identification
- 6525 Communication link, telemetry expander
- 2092 Gear set (for 2090 servo)
- 2968X LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
- 2968 LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)
- 6535 Mount, temperature sensor (electric motors)/ wire tie/ thermal pad
- 6533 Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)

- 6552 Seal kit, expander box (includes o-ring, seals, and silicone grease)
- 6526 Sensor, auto-detectable, temperature
- 6527 Sensor, auto-detectable, voltage
- 6521 Sensor, temperature and voltage (long)
- 2091 Servo case/ gaskets (for 2090 waterproof servo)
- 2090 Servo, digital high-torque (ball bearing), waterproof
- 6553X Telemetry Expander 2.0 and GPS module 2.0, TQi radio system
- 6550X Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module)
- 6551X Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)
- 6509R TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)
- 6507R TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)
- 6528 Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-channel (transmitter only)
- 6529 Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-channel (transmitter only)
- 6530 Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-channel (transmitter only)
- 6511 Traxxas® Link Bluetooth® module

Ready-To-Race Model

- 89086-4 Maxx®: 1/10 Scale 4WD Brushless Electric Monster Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®

Rear Suspension

- 8927 Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) (steel)
- 8928 Bulkhead, rear (upper and lower)
- 8952X Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) (2)
- 8952G Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear) (2)
- 8952 Carriers, stub axle (left & right)
- 8952A Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rear) (2)
- 8952R Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2)
- 8916 Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2)
- 8958 Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)
- 8939 Shock tower, rear (left & right halves)
- 8999 Suspension arms, lower, black (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999X Suspension arms, lower, blue (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999G Suspension arms, lower, green (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999T Suspension arms, lower, orange (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999R Suspension arms, lower, red (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998 Suspension arms, upper, black (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998X Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998G Suspension arms, upper, green (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998T Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998R Suspension arms, upper, red (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 7743 Suspension pin retainer (4)
- 8940X Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
- 8943 Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)
- 8941 Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
- 8940 Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)

Shock Oil

- 5031 Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
- 5032 Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
- 5033 Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
- 5034 Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
- 5035 Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
- 5036 Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
- 5037 Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)

Page 4 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89086-4) Parts List

- 5029 Shock oil bottle (60cc) (for mixing shock oil)
5038X Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)
5038 Spinning carousel rack

Shocks (GT-Maxx®)

- 8965X Body, GT-Maxx® shock (aluminum, blue-anodized) (1)
8965G Body, GT-Maxx® shock (aluminum, green-anodized) (1)
8965T Body, GT-Maxx® shock (aluminum, orange-anodized) (1)
8965R Body, GT-Maxx® shock (aluminum, red-anodized) (1)
8962 Rebuild kit, GT-Maxx® shocks (lower cartridge, pistons, piston nuts, bladders, screws) (renews 2 shocks)
8964X Shock caps, aluminum (blue-anodized), GT-Maxx®, shocks (4)
8964G Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4)
8964T Shock caps, aluminum (orange-anodized), GT-Maxx® shocks (4)
8964R Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4)
8964 Shock caps, GT-Maxx® shocks/ spring perch/ adjusters (2) (for 2 shocks)
8963 Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends (2)/ hollow balls (2)
8963T Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with rod ends and steel hollow balls)
9660 Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled w/o springs) (2)
8961G Shocks, GT-Maxx®, aluminum (green-anodized) (fully assembled w/o springs) (2)
8961T Shocks, GT-Maxx®, aluminum (orange-anodized) (fully assembled w/o springs) (2)
8961R Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o springs) (2)
8968X Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968G Spring retainer (adjuster), green-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968A Spring retainer (adjuster), orange-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8968R Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® shocks (4) (assembled with o-ring)
8966 Springs, shock (natural finish) (GT-Maxx®) (1.210 rate) (2)
8967 Springs, shock (natural finish) (GT-Maxx®) (1.450 rate) (2)
8969 Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2)
8959 Springs, shock (natural finish) (GT-Maxx®) (2.054 rate) (2)

Spur Gears & Pinion Gears

- 6487X Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6489X Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6490X Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6491X Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6491R Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6494X Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6494R Gear, 20-T pinion (machined, hardened steel) (1.0 metric pitch) (fits 5mm shaft)/ set screw
6495X Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6481X Gear, 23-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6496X Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6492X Gear, 25-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
6497 Gear, 26-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6447 Spur Gear, 46-tooth (1.0 metric pitch)
6442 Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
6447R Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
6448 Spur Gear, 50-tooth (1.0 metric pitch)
6443 Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
6448R Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
6449 Spur Gear, 54-tooth (1.0 metric pitch)
6444 Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 metric pitch)
6449X Spur gear, 54-tooth, steel (1.0 metric pitch)
6449R Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)

Steering Components

- 2728 Ball bearings (5x8x2.5mm) (2)
7020 Ball bearings, blue rubber sealed (8x12x3.5mm) (2)

- 8947X Servo horn, steel
8947 Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls)
8946 Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2)
8997X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

Suspension Linkage

- 8958 Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X)
7743 Suspension pin retainer (4)
8940X Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8)
8942 Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1)
8943 Suspension pin set, rear (left or right) (hardened steel), 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1)
8941 Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened steel)
8940 Suspension screw pin set, front or rear (hardened steel), 4x18mm (4), 4x38mm (2), 4x33mm (2), 4x43mm (2)
8997X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8997R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

Team Traxxas Items

- 2514 Decal sheet, racing sponsors
9950 Official Team Traxxas® racing decal set(flag logo/ 6-color)
9909 Traxxas® racing banner, red & black (3x7 feet)

Tires & Wheels

- 8447A Nuts, 5mm flanged nylon locking (aluminum, black-anodized, serrated) (4)
8447X Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, serrated) (4)
8447G Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)
8447R Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4)
8447 Nuts, 5mm flanged nylon locking (steel, black serrated) (8)
5147X Nuts, 5mm flanged nylon locking (steel, serrated) (8)
8973 Tires & wheels, assembled, glued (black wheels, dual profile (2.8" outer, 3.6" inner), Sledgehammer® tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972 Tires & wheels, assembled, glued (black wheels, Maxx® All-Terrain tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972A Tires & wheels, assembled, glued (black, blue beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972T Tires & wheels, assembled, glued (black, orange beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972R Tires & wheels, assembled, glued (black, red beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8972X Tires & wheels, assembled, glued (black, satin chrome beadlock style wheels, Maxx® MT tires, foam inserts) (2) (17mm splined) (TSM® rated)
8970 Tires, Maxx® All-Terrain 2.8" (2)/ foam inserts (2)

Page 5 Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 89086-4) Parts List

- 8974 Tires, Sledgehammer® (2)/ foam inserts (2)
- 8956 Wheel hubs, hex (2)/ 2.5x14 pins (2)
- 8956X Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4)
- 8956G Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm screw pins (4)
- 8956T Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4)
- 8956R Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4)
- 8654 Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8654G Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8654A Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4)
- 8654R Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4)
- 8957 Wheel washers (4)
- 8957X Wheel washers, blue (4)
- 8957G Wheel washers, green (4)
- 8957T Wheel washers, orange (4)
- 8957R Wheel washers, red (4)
- 8971 Wheels (black) (2)

Transmission Components

- 8987 Covers, gear (2)
- 8985 Input gear, transmission, 22-tooth/ 2.5x12mm pin
- 8986 Input shaft, transmission
- 5040 Oil, differential (20M wt) (standard)

Traxxas Tools

- 3433X Body reamer (aluminum handle)
- 3433 Body reamer (plastic handle)
- 3436 Cap, body reamer
- 3432 Scissors, curved tip
- 3431 Scissors, straight tip
- 8712 Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
- 8720 Speed bit handle, large (overmolded)
- 8721 Speed bit handle, medium (one piece)
- 8722 Speed bit handle, premium (rubber overmold)
- 8710 Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
- 8711 Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
- 8719 Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
- 8716 Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
- 8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive
- 8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
- 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
- 8714 Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits), 1/4" drive
- 2748R Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench)
- 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm, 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)

Turnbuckles & Threaded Rods

- 8948X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)

- 8948R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1)
- 8948 Toe links, molded composite, 100mm (89mm center to center) (black) (2)

WideMaxx™ Suspension Kit

- 8996 Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) (for use with #8995 WideMaxx™ suspension kit)
- 8996R Driveshaft, steel constant velocity (shaft only, 109.5mm) (1) (replacement shaft for #8996X)
- 8996A Driveshaft, steel constant-velocity (shaft only, 109.5mm) (4) (for conversion of #8950X driveshafts to WideMaxx® suspension)
- 8996X Driveshafts, steel constant-velocity (assembled), front or rear (4) (for use with #8995 WideMaxx® suspension kit) (requires #8654 series 17mm splined wheel hubs and #7758 series 17mm nuts for a complete set)
- 8993 Half shaft set, left or right (plastic parts only) (internal splined half shaft/ external splined half shaft) (4 assemblies) (for use with #8995 WideMaxx™ suspension kit)
- 8993A Half shafts, outer (extended, front or rear) (4)/ e-clips (8) (for use with #8995 WideMaxx™ suspension kit)
- 8994 Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) (for use with #8995 WideMaxx™ suspension kit)
- 8999 Suspension arms, lower, black (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999X Suspension arms, lower, blue (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999G Suspension arms, lower, green (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999T Suspension arms, lower, orange (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8999R Suspension arms, lower, red (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998 Suspension arms, upper, black (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998X Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998G Suspension arms, upper, green (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998T Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8998R Suspension arms, upper, red (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit)
- 8995 Suspension kit, WideMaxx®, black (includes front & rear suspension arms, front toe links, outer half shafts (extended), rear shock springs)
- 8995X Suspension kit, WideMaxx®, blue (includes front & rear suspension arms, front toe links, outer half shafts (extended), rear shock springs)
- 8995G Suspension kit, WideMaxx®, green (includes front & rear suspension arms, front toe links, outer half shafts (extended), rear shock springs)
- 8995T Suspension kit, WideMaxx®, orange (includes front & rear suspension arms, front toe links, outer half shafts (extended), rear shock springs)
- 8995A Suspension kit, WideMaxx®, white (includes front & rear suspension arms, front toe links, outer half shafts (extended), rear shock springs)
- 8997 Toe links, 119.8mm (108.6mm center to center) (black) (2) (for use with #8995 WideMaxx® suspension kit)
- 8997X Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
- 8997G Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
- 8997A Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)
- 8997R Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM