XXAY XI34'15 SET-UP SHEET RACE **BASIC SET-UP** REAR UPRIGHT SHOCK TOWER TRACK STANDARD 🔀 NAME DATE LOWER → SHIM DRIVE SHAFT SHIM STANDARD 🔀 0 STEERING BLOCK LAPS **BEST LAP TIME** MEDIUM **DRIVE SHAFT** QUALIFYING POSITION **FINAL POSITION** HARD STANDARD 🔀 SHIM X GRAPHITE TRACK SIZE OPEN MEDIUM TIGHT 2 ROLL ENTER LONGER BUSHINGS TRACK TRACTION 2**8** 7 HIGH Low MEDIUN X UP (0) TRACK SURFACE (0) SMOOTH MEDIUM BUMPY REAR UPRIGHT DOWN MEDIUM TRACK TYPE <u></u> HARD PACKED SOFT DIRT CLAY X HARD LOWER SHOCK POSITION CARPET BLUE GROOVE ASTRO TURF GRASS 1° 0.5 GRAPHITE TRACK CONDITION DOWNSTOP #107701 SUPPORT BLOCKS DOWNSTOP ALU DRY DUSTY WET MUD **DIFFERENTIAL TYPE** CASTER CASTER BLOCK SHOCK TOWER CASTER FRONT POSITION 6° MEDIUM FRONT 🔀 🔲 REAR GEAR DIFF GEAR DIFF 🔀 GEAR DIFF 9° X HARD X BALL DIFF SLIPPER 🗶 BALL DIFF 12° GRAPHITE **SHOCK POSITION** 10K FRONT 🔀 🔲 REAR OIL 10K OFFSET ALU SATELLITE GEARS **BUMP STEER SHIM** COMPOSITE 🗶 сомроѕіте Г COMPOSITE OFFSET STEEL STEEL STEEL 0 SLIPPER **CROWN GEAR CROWN GEAR** RAISING GEARBOX **UPRIGHT WHEELBASE** /slots COMPOSITE COMPOSITE 0.5 SHIM YES 🔲 🗶 NO STEEL 🗶 STEEL LIPPER ADJUSTMENT IN FRONT OF ARM RONT ALU ALU 🔀 ALU COMPOSITE COMPOSITE ROLL CENTER PINION - RF --0.5° 0.5° ☐ BRASS X STEEL STEEL 🗶 2mm 🗶 🔲 0mm ECCENTRIC BUSHINGS GEARING X ALU RR ☐ BRASS PINION SPUR GEAR 81 0.5° 0.5° SHOCKS RONT REAR OUT FRONT TOE REAR TOE **SPRINGS** 3 DOTS 2 DOTS 700 OIL 500 0 **REBOUND** 0 **BUMP STEER SHIM GRAPHITE FOR** REAR BRACE **PISTONS ARM SHIM** OPTIONAL ALU STEERING PLATE YES ø1.2mm X 2 HOLES ... 2 HOLES 🔀 #362574 NO ø1.3mm SERVO SAVER ☐ 3 HOLES **⑥** 3 HOLES 🗌 ø1.4mm SOFT REAR BRACE ARM SHIM UPPER PLATE MFDIUM X MEDIUN ø1.6mm TIGHT ☐ 6 HOLES Ø1.7mm X 6 HOLES 🔲 STANDARD HARD MATERIAL STEERING BRACE 🔀 **CUSTOM PISTONS ₩ E** STANDARD X **ERONT** REAR RONT **ANTI ROLL BAR** REAR FRONT ARM REAR ARM FRONT CAMBER REAR CAMBER THICKNESS 1.2 MEDIUM MEDIUM П 0 HARD X HARD 0 REAR RONT TIRES GRAPHITE GRAPHITE **BRAND** DOWNSTOP SHIM DOWNSTOP SHIM COMPOUND **INSERTS** D/2 LENGTH LENGTH **XRAY** WHEELS XRAY **ELECTRONICS UPSTOP SHIM UPSTOP SHIM** RIDE HEIGHT RIDE HEIGHT RIDE HEIGHT MOTOR **SPEEDO** 16 MOTOR TIMING BATTERY REAR BODY BALANCE CHASSIS BALANCE **ELECTRONICS LAYOUT** STANDARD 🔀 STANDARD 🔀 8 WING THICKNESS MOTOR POSITION FRONT X REAR LIGHT ψ **BATTERY POSITION** FRONT X REAR 1.5mm 2.0mm 1.0mm **BATTERY SIZE** STD. SHORT LOW SHORT TYPE **COMMENTS** ( WING CUTTING LINE 0 **CHASSIS FLEX** SIDE GUARDS SCREW USED MEDIUM SCREW NOT USED BALANCE BALANCE HARD GRONT REAR