

HOT NEW ITEMS FOR

X-MAXX



RED-ANODIZED GTX SHOCKS

Complete GTX shock assemblies with red anodized shock bodies. Sold in pairs. Springs sold separately.

7761R - GTX Shock (Red, 2)



ALUMINUM WHEEL HUBS

Replaces the stock plastic wheel hexes with the ruggedness and good looks of red or blue-anodized aluminum.

7756R - Hubs (Red, 4) 7756X - Hubs (Blue, 4)



GTX PTFE SHOCK BODIES

Hard-anodized and PTFE-coated for long-lasting, ultra-smooth damping performance. One per package.

7765X - Shock Body (PTFE)



RED STUB AXLE & WHEEL NUTS

Stock aluminum X-Maxx stub axles and wheel nuts are now available in red. The wheel nuts also fit Revo and Summit series.

7753R - Stub Axle (Red, 1) 7758R - Wheel Nuts (Red, 4)



GTX SHOCK SPRING RETAINERS

Red or blue-anodized aluminum upper spring retainers are equipped with an integrated o-ring for dialing in precise spring pre-load adjustment.

7767 - Retainer (Adjuster) (Blue, 4)
7767R - Retainer (Adjuster) (Red, 4)



STEEL SPUR GEAR

Steel delivers the ultimate in durability and heat resistance for the X-Maxx spur gear.

6449X - 54-T



GTX ALUMINUM SHOCK CAPS

Aluminum shock caps add strength to X-Maxx shocks. Available in red, blue, or PTFE-coated.

7764A - Shock Caps (Blue, 4)
7764R - Shock Caps (Red, 4)
7764X - GTX Shock Caps (PTFE-coated, 4)



PINION GEARS

Fine tune X-Maxx gear ratios with genuine Traxxas precision pinion gears.

6484 - 11-T 6485 - 12-T
6486 - 13-T



GTX SHOCK SHAFTS

Titanium-nitride coated shafts resist scuffing, increase durability, and eliminate "stiction." Sold in pairs with precision rod ends conveniently installed.

7763T - TiN-Coated (2)



MOTOR MOUNT WASHERS

Specially engineered aluminum washers add additional strength and good looks to the motor mounts in the X-Maxx chassis.

7759 - Washers w/ Hardware (Blue)
7759R - Washers w/ Hardware (Red)



STANDARD SERVO ADAPTER

X-Maxx servo adapter allows the installation of a standard-size servo in the X-Maxx chassis.

7749 - X-Maxx Servo Adapter

**SEE PAGE 2 FOR
COMPLETE ACCESSORIES LISTING**



Part No. Description

6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx)
7759	Washers, motor mount, aluminum (blue-anodized) (4)/ 4x18mm BCS (4)
7759R	Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm BCS (4)
7765X	Body, GTX shock (aluminum, hard-anodized, PTFE-coated) (1)

Part No. Description

6484	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6485	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6486	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
7756X	Wheel hubs, hex, aluminum (blue-anodized) (4)
7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
7763T	Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and hollow balls)
7767	Spring retainer (adjuster), blue-anodized aluminum, GTX shocks (4) (assembled with o-ring)
7767R	Spring retainer (adjuster), red-anodized aluminum, GTX shocks (4) (assembled with o-ring)
7767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks (4) (assembled with o-ring)

Part No. Description

7753R	Stub axle, aluminum, red-anodized (1)
7756R	Wheel hubs, hex, aluminum (red-anodized) (4)
7761R	Shocks, GTX, aluminum, red-anodized (fully assembled w/o springs) (2)
7764A	Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers (8)
7764R	Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers (8)
7764X	Shock caps, aluminum (hard-anodized, PTFE-coated), GTX shocks (4)/ spacers (8)