

SPEKTRUM SERVOS

| MODEL | DESCRIPTION | GEAR TYPE | BEARING | TORQUE/FORCE HIGH VOLTAGE 8.4V (2S LI-PO) | SPEED HIGH VOLTAGE 8.4V (2S LI-PO) | DIMENSIONS (L x W x H) in/mm | WEIGHT oz/g | AIRCRAFT | SURFACE |
|----------------------------------|--|-------------|-------------|--|---|--|------------------|----------|---------|
| AIRPLANE | | | | | | | | | |
| SPMSA6110 | A6110 HV Standard | Nylon | Single BB | 76 oz-in (5.5 kg-cm) | 0.14 sec/60° | 1.50 x 0.72 x 1.44 in (38.3 x 18.4 x 36.6mm) | 1.28 oz (36.5 g) | ✓ | |
| SPMSA6150 | A6150 HV Hi-Torque MG | Metal | Dual BB | 180 oz-in (13.0 kg-cm) | 0.12 sec/60° | 1.57 x 0.79 x 1.51 in (40.0 x 20.0 x 38.3mm) | 1.90 oz (53.9 g) | ✓ | |
| SPMSA6180 | A6180 Digital | Metal | Dual BB | 94 oz-in (6.8 kg-cm) @ 6.0V | 0.14 sec/60° @ 6.0V | 1.53 x 0.74 x 1.37 in (38.8 x 18.8 x 34.9mm) | 1.48 oz (42.0 g) | ✓ | |
| SPMSA6220 | A6220 HV Low-Profile Hi-Torque MG | Metal | Dual BB | 140 oz-in (10.1 kg-cm) | 0.11 sec/60° | 1.58 x 0.79 x 1.02 in (40.3 x 20.0 x 26.0mm) | 1.60 oz (46.0 g) | ✓ | |
| SPMSA6265 | A6265 HV Digital Hi-Torque MG Aircraft Servo | Metal | Dual BB | 328 oz-in (23.6 kg-cm) | 0.15 sec/60° @ 6.0V | 1.61 x 0.82 x 1.25 in (40.9 x 20.9 x 31.8mm) | 2.20 oz (62.0g) | ✓ | |
| SPMSA6270 | A6270 HV Ultra Torque MG | Steel | Dual BB | 582 oz-in (41.9 kg-cm) | 0.12 sec/60° | 1.61 x 0.82 x 1.35 in (40.9 x 20.9 x 34.3mm) | 2.70 oz (76.5 g) | ✓ | |
| SPMSA4010 | A4010 Micro Digital | Nylon | Single BB | 42 oz-in (3.0kg-cm) @ 6.0V | 0.11 sec/60° @ 6.0V | 1.10 x 0.50 x 1.07 in (28.0 x 12.7 x 27.4mm) | 0.60 oz (17.2 g) | | ✓ |
| SPMSA4030 | A4030 Micro HV Digital Hi-Torque MG | Metal | Dual BB | 83.3 oz-in (6.0 kg-cm) | 0.10 sec/60° | 1.10 x 0.50 x 1.07 in (28.0 x 12.7 x 27.4mm) | 0.71 oz (20.0 g) | | ✓ |
| SPMSA5030 | A5030 Mini Digital | Nylon | Dual BB | 66 oz-in (4.8 kg-cm) @ 6.0V | 0.10 sec/60° @ 6.0V | 1.30 x 0.58 x 1.10 in (33.0 x 15.0 x 28.0mm) | 0.83 oz (23.6 g) | ✓ | |
| SPMSA5040 | A5040 Mini Digital MG | Metal | Dual BB | 66 oz-in (4.8 kg-cm) @ 6.0V | 0.10 sec/60° @ 6.0V | 1.30 x 0.58 x 1.10 in (33.0 x 15.0 x 28.0mm) | 0.76 oz (21.6 g) | ✓ | |
| SPMSA5060 | A5060 Mini HV Digital Hi-Torque MG | Metal | Dual BB | 118 oz-in (8.5 kg-cm) | 0.11 sec/60° | 1.30 x 0.58 x 1.08 in (32.8 x 14.7 x 27.4mm) | 0.92 oz (26.0 g) | ✓ | |
| SPMSA2010 | A2010 Ultra Micro | Nylon | Single BB | 2.5 oz-in (0.18kg-cm) @ 4.8V | 0.06 sec/60° @ 4.8V | 0.71 x 0.31 x 0.67 in (18.1 x 8.00 x 16.9mm) | 0.09 oz (2.50 g) | | ✓ |
| SPMSA2020 | A2020 Nanolite | Nylon | Single BB | 12 oz-in (0.86 kg-cm) @ 4.8V | 0.08 sec @ 4.8V | 0.78 x 0.33 x 0.90 in (19.7 x 8.30 x 22.8mm) | 0.14 oz (4.10 g) | | ✓ |
| SPMSA3030 | A3030 Sub-Micro Digital Hi-Torque | Nylon | Single BB | 28 oz-in (2 kg-cm) @ 6.0V | 0.10 sec/60° @ 6.0V | 0.93 x 0.45 x 1.00 in (23.6 x 11.5 x 25.5mm) | 0.30 oz (8.60 g) | | ✓ |
| SPMSA3040 | A3040 Sub-Micro Digital Hi-Torque MG | Metal | Single BB | 28 oz-in (2 kg-cm) @ 6.0V | 0.10 sec/60° @ 6.0V | 0.93 x 0.45 x 1.00 in (23.6 x 11.5 x 25.5mm) | 0.44 oz (12.6 g) | | ✓ |
| SPMSA7020 | A7020 Digital Thin Wing | Metal | Dual BB | 50 oz-in (3.6 kg-cm) @ 6.0V | 0.09 sec/60° @ 6.0V | 1.08 x 0.39 x 1.07 in (27.4 x 10.0 x 27.2mm) | 0.50 oz (14.5 g) | ✓ | |
| SPMSA7040 | A7040 HV Retract | Metal | Dual BB | 266 oz-in (19.2 kg-cm) | 1.39 sec/160° | 1.70 x 0.87 x 1.07 in (44.0 x 22.2 x 27.3mm) | 1.48 oz (42.0 g) | ✓ | |
| SPMSA7050 | A7050 HV Thin Wing | Metal | Dual BB | 65 oz-in (4.70 kg-cm) | 0.07 sec/60° | 1.08 x 0.40 x 1.06 in (27.4 x 10.2 x 27.0mm) | 0.70 oz (20.0 g) | ✓ | |
| SPMSA2005 | 1.8-Gram Linear | Nylon | 2 BBs | 2.8 oz (79.4 g) @ 4.2V | 0.14 sec @ 4.2V | 0.60 x 0.59 x 0.33 in (16.0 x 15.0 x 8.20mm) | 0.06 oz (1.80 g) | ✓ | |
| SPMSA2030L | 2.3-Gram Performance Linear Long Throw | Nylon | Single BB | 3.5 oz (100 g) @ 4.2V | 0.14 sec @ 4.2V | 0.87 x 0.66 x 0.33 in (22.0 x 16.9 x 8.20mm) | 0.10 oz (2.30 g) | ✓ | |
| SPMSA2030LO | 2.3-Gram Linear Long Throw Offset | Nylon | Single BB | 3.5 oz (100 g) @ 4.2V | 0.14 sec @ 4.2V | 0.87 x 0.66 x 0.33 in (22.0 x 16.9 x 8.20mm) | 0.10 oz (2.30 g) | ✓ | |
| HELICOPTER | | | | | | | | | |
| SPMSH6160 | H6160 HV High Speed Cyclic MG | Metal | Dual BB | 132 oz-in (9.5 kg-cm) | 0.11 sec/60° | 1.57 x 0.79 x 1.51 in (40.0 x 20.0 x 38.3mm) | 1.90 oz (53.9 g) | | ✓ |
| SPMSH6205 | H6205 HV Digital High Speed Heli Cyclic MG | Metal | Dual BB | 166 oz-in (12.0kg-cm) | 0.07 sec/60° @ 6.0V | 1.61 x 0.82 x 1.25 in (40.9 x 20.9 x 31.8mm) | 2.20 oz (61.7g) | | ✓ |
| SPMSH6210 | H6210 HV Digital Ultra Speed Tail MG | Steel | Dual BB | 107 oz-in (7.7 kg-cm) | 0.03 sec/60° | 1.61 x 0.82 x 1.25 in (40.9 x 20.9 x 31.8mm) | 2.20 oz (62.4 g) | | ✓ |
| SPMSH6280 | H6280 HV Ultra Speed Cyclic MG | Steel | Dual BB | 280 oz-in (13.5 kg-cm) | 0.06 sec/60° | 1.61 x 0.82 x 1.35 in (40.9 x 20.9 x 34.3mm) | 2.70 oz (76.5 g) | | ✓ |
| SPMSH3020 | H3020 Sub-Micro High-Speed MG | Metal | Single BB | 22 oz-in (1.6 kg-cm) @ 6.0V | 0.08 sec/60° @ 6.0V | 0.93 x 0.45 x 1.00 in (23.6 x 11.5 x 25.5mm) | 0.44 oz (12.6 g) | | ✓ |
| SPMSH3050 | H3050 Sub-Micro Digital Heli Cyclic MG Servo | Metal | Single BB | 29 oz-in (2.1kg-cm) @ 4.8V | 0.067 sec/60° @ 4.8V | 0.91 x 0.47 x 1.17in (23.0 x 12.0 x 29.6mm) | 0.46 oz (12.9 g) | ✓ | |
| SPMSH3060 | H3060 Sub-Micro Digital Heli Tail MG Servo | Metal | Single BB | 12 oz-in (0.9kg-cm) @ 4.8V | 0.036 sec/60° @ 4.8V | 0.91 x 0.47 x 1.17in (23.0 x 12.0 x 29.6mm) | 0.46 oz (12.9 g) | | |
| SPMSH2025L | 2.0-Gram Linear Long-Throw, 15mm Lead | Nylon | Single BB | 3.5 oz (100 g) @ 4.2V | 0.14 sec @ 4.2V | 0.87 x 0.66 x 0.33 in (22.0 x 16.9 x 8.20mm) | 0.07 oz (2.00 g) | ✓ | |
| SPMSH2026L | 2.1-Gram Linear Long-Throw, 38mm Lead | Nylon | Single BB | 3.5 oz (100 g) @ 4.2V | 0.14 sec @ 4.2V | 0.87 x 0.66 x 0.33 in (22.0 x 16.9 x 8.20mm) | 0.07 oz (2.10 g) | ✓ | |
| SPMSH2040L | 2.9-Gram Linear Long Throw | Nylon | Single BB | 11.6 oz (329 g) @ 4.2V | 0.13 sec @ 4.2V | 0.90 x 0.70 x 0.40 in (24.0 x 19.0 x 9.00mm) | 0.10 oz (2.90 g) | ✓ | |
| SPMSH2040T | 2.9-Gram Linear Tail | Nylon | Single BB | 9.6 oz (272 g) @ 4.2V | 0.065 sec @ 4.2V | 0.90 x 0.70 x 0.40 in (24.0 x 19.0 x 9.00mm) | 0.10 oz (2.90 g) | ✓ | |
| SPMSH2060 | H2060 Nanolite High Speed Cyclic | Nylon | Bushing | 11.4 oz (323 g) @ 6.0V | 0.07 sec/60° @ 6.0V | 0.90 x 0.70 x 0.40 in (19.6 x 8.15 x 25.0mm) | 0.14 oz (4.00 g) | ✓ | |
| CAR / TRUCK / BOAT | | | | | | | | | |
| WATERPROOF/ RESISTANT | | | | | | | | | |
| SPMSS6020 | S6020 Digital—Torque | Metal/Nylon | Dual BB | 146 oz-in (10.5 kg-cm) @ 6.0V | 0.19 sec/60° @ 6.0V | 1.61 x 0.79 x 1.53 in (41.0 x 20.0 x 39.0mm) | 1.73 oz (49.0 g) | | ✓ |
| SPMSS6170 | S6170 Standard Digital | WP | Nylon | 80 oz-in (5.8 kg-cm) @ 6.0V | 0.14 sec/60° @ 6.0V | 1.51 x 0.73 x 1.36 in (38.4 x 18.5 x 34.5mm) | 1.20 oz (32.0 g) | | ✓ |
| SPMSS6180 | S6180 Standard Digital MG | WP | Brass/Metal | 100 oz-in (7.2 kg-cm) @ 6.0V | 0.14 sec/60° @ 6.0V | 1.51 x 0.74 x 1.36 in (38.4 x 18.8 x 34.5mm) | 1.50 oz (42.0 g) | | ✓ |
| SPMSS6230 | S6230 Digital Surface Servo | WP | Metal | 311 oz-in (22.4kg-cm) @ 6.0V | 0.14 sec/60° @ 6.0V | 1.61 x 0.82 x 1.18 in (41.0 x 20.8 x 30.0mm) | 2.10 oz (59.5g) | ✓ | ✓ |
| SPMSS6240 | S6240 High Speed, Dig Servo | WP | Metal | 208 oz-in (15.0kg-cm) @ 6.0V | 0.08 sec/60° @ 6.0V | 1.61 x 0.82 x 1.18 in (41.0 x 20.8 x 30.0mm) | 2.10 oz (59.5g) | ✓ | ✓ |
| SPMSS6250 | S6250 High Torque, HV Dig Servo | WP | Metal | 382 oz-in (27.5kg-cm) @ 8.4V | 0.09 sec/60° @ 8.4V | 1.61 x 0.82 x 1.18 in (41.0 x 20.8 x 30.0mm) | 2.10 oz (59.5g) | | ✓ |
| SPMSS6260 | S6260 High Speed, HV Dig Servo | WP | Metal | 241 oz-in (17.4kg-cm) @ 8.4V | 0.06 sec/60° @ 8.4V | 1.61 x 0.82 x 1.18 in (41.0 x 20.8 x 30.0mm) | 2.10 oz (59.5g) | | ✓ |
| SPMSS6270 | S6270 HV Low-Profile Race Digital MG | WP | Metal | 174 oz-in (12.5 kg-cm) | 0.05 sec/60° | 1.61 x 0.82 x 1.06 in (41.0 x 20.9 x 26.7mm) | 1.50 oz (42.0 g) | | ✓ |
| SPMSS6280 | S6280 Ultra Torque, HV Dig Servo | WP | Metal | 496 oz-in (35.7kg-cm) @ 8.4V | 0.10 sec/60° @ 8.4V | 1.61 x 0.82 x 1.38 in (41.0 x 20.9 x 26.7mm) | 2.80 oz (79.4g) | | ✓ |
| SPMSS6290 | S6290 Ultra Speed, HV Dig Servo | WP | Metal | 331 oz-in (23.8kg-cm) @ 8.4V | 0.07 sec/60° @ 8.4V | 1.61 x 0.82 x 1.38 in (41.0 x 20.9 x 26.7mm) | 2.80 oz (79.4g) | | ✓ |
| SPMSS9010 | S9010 HV 1/5-Scale Digital—Throttle | WP | Steel | 660 oz-in (47.5 kg-cm) | 0.11 sec/60° no load | 3.00 x 1.20 x 1.80 in (75.0 x 30.0 x 45.5mm) | 5.00 oz (142 g) | | ✓ |
| SPMSS9020 | S9020 HV 1/5-Scale Digital—Steering | WP | Steel | 1000 oz-in (72 kg-cm) | | | | | |