


#89568 Optional Gear Set Conversion Chart

This new ring and pinion gear set provides an optional gear ratio that smooths out power delivery of both 1:8 gas and electric vehicles. Each vehicle type requires two sets. For RC8, RC8.2, RC8.2e, SC8, and SC8.2e kits and RTRs.

The new final drive ratio introduced by the Optional Gear Set requires a change in your gearing.

Step 1 If using the Standard ("Std") gear set, find your current combination of spur gear (green column) and clutch bell/pinion (white column).



Step 2: When using #89568 Optional Gear Set, use the clutch bell listed under the "Optional" column to the right of your "Std" clutch bell/pinion value.

Model	Spur	Gas Clutch Bell or Electric Pinion											
		Std	Optional	Std	Optional	Std	Optional	Std	Optional	Std	Optional	Std	Optional
RC8.2 SC8.2	44	15	12	16	12	17	13	18	14	19	15	20	15
	46	15	12	16	12	17	13	18	14	19	15	20	15
	48	15	12	16	12	17	13	18	14	19	15	20	15

Model	Spur	Gas Clutch Bell or Electric Pinion											
		Std	Optional	Std	Optional	Std	Optional	Std	Optional	Std	Optional	Std	Optional
RC8T	48	13	10	14	11	15	12	16	12	17	13	18	14
	50	13	10	14	11	15	12	16	12	17	13	18	14
	52	13	10	14	11	15	12	16	12	17	13	18	14