

# ABSIMA "Revenge CTM" Series

Competition Brushless Motors



Approved for:	Touring Car; 4WD Buggy 1/10*				Touring Car; 2WD / 4WD Buggy 1/10*			2WD Buggy / Truck / SC 1/10*		2WD Buggy / Truck / SC - stock classes 1/10*			
Part no.:	<b>2130010</b>	<b>2130011</b>	<b>2130012</b>	<b>2130013</b>	<b>2130014</b>	<b>2130015</b>	<b>2130016</b>	<b>2130017</b>	<b>2130018</b>	<b>2130019</b>	<b>2130020</b>	<b>2130021</b>	<b>2130022</b>
Turns:	<b>3,5T</b>	<b>4,0T</b>	<b>4,5T</b>	<b>5,0T</b>	<b>5,5T</b>	<b>6,5T</b>	<b>7,5T</b>	<b>8,5T</b>	<b>9,5T</b>	<b>10,5T</b>	<b>13,5T</b>	<b>17,5T</b>	<b>21,5T</b>
RPM-V:	9430	8250	7330	6690	6080	5480	5150	4660	4135	3730	3040	2270	1850
Power:	710W	620W	560W	550W	500W	450W	410W	380W	350W	320W	255W	190W	150W
Current A:	93A	86A	77A	73A	68A	62A	56A	50A	47A	45A	35A	27A	20A
Efficiency:	88%	90%	90%	90%	92%	93%	93%	93%	93%	94%	94%	95%	95%
Voltage:	1-2S	1-2S	1-2S	1-2S	1-3S	1-3S	1-3S	1-3S	1-3S	1-3S	1-3S	1-3S	1-3S
Poles:	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole	2 Pole
Sensor:	Yes												
Adjust. timing:	Yes												
Ø w/o fins:	36 mm												
Shaft diameter:	3,175 mm / 48db												
Shaft length:	15,8 mm												
Length:	53 mm												
Weight:	178 gr												

Approved for:	Short Course 4WD 540size - 4 Pole*	
Part no.:	<b>2130030</b>	<b>2130031</b>
Turns:	<b>4300 KV</b>	<b>4800 KV</b>
RPM-V:	4300	4800
Power:	530W	620W
Current A:	70A	80A
Efficiency:	93%	92%
Voltage:	1-3S	1-2S
Poles:	4 Pole	4Pole
Sensor:	Yes	
Adjust. timing:	Yes	
Ø w/o fins:	36mm	
Shaft diameter:	5mm / Module 1	
Shaft length:	18,8mm	
Length:	53mm	
Weight:	180gr	

Approved for:	Short Course 4WD 550size - 2 Pole*		
Part no.:	<b>2130032</b>	<b>2130033</b>	<b>2130034</b>
Turns:	<b>4.0T</b>	<b>4.5T</b>	<b>5.0T</b>
RPM-V:	5140	4520	4150
Power:	950W	900W	850W
Current A:	133A	126A	120A
Efficiency:	92%	92%	94%
Voltage:	2S	2S	2-3S
Poles:	2 Pole	2 Pole	2 Pole
Sensor:	Yes		
Adjust. timing:	Yes		
Ø w/o fins:	36mm		
Shaft diameter:	5mm / Module 1		
Shaft length:	15,3mm		
Length:	63mm		
Weight:	189gr		

Approved for:	1:8 Scale*			
Part no.:	<b>2130040</b>	<b>2130041</b>	<b>2130042</b>	<b>2130043</b>
Turns:	<b>1750 KV</b>	<b>2100 KV</b>	<b>2300 KV</b>	<b>2500 KV</b>
RPM-V:	1750	2100	2300	2500
Power:	1670W	2070W	2100W	2650W
Current A:	110A	125A	145A	160A
Efficiency:	88%	88%	88%	86%
Voltage:	4-6S	4-6S	4-6S	3-4S
Poles:	4 Pole	4 Pole	4 Pole	4 Pole
Sensor:	Yes			
Adjust. timing:	Yes			
Ø w/o fins:	42mm			
Shaft diameter:	5mm / Module 1			
Shaft length:	18,3mm			
Length:	69mm			
Weight:	320gr			

\*Sensor cable is included