

Transmitters		FASST Receivers						FASSTest Receivers	Protocol Selection
		R603FF R603FS	R604FS R614FF R614FS R614FF-E	R606FS	R6004FF R616FFM R6106HF R6106HFC R607FS R617FS	R608FS R6008HS R6014FS R6014HS R6108SB R6208SB	R6203SB R6203SBE R6202SBW R6303SB R6303SBE	R7003SB R7008SB	
3PM 2.4GHz		X							
3PKS 2.4GHz		X							
3VCS 2.4GHz		X							
3GR 2.4GHz		X							
4PK / 4PKS / 4PKSR 2.4GHz	C1 Mode	X							Via Screen Selection
	C2 Mode		X						Via Screen Selection
6EX 2.4GHz				X	X		X		
7C 2.4GHz				X	X		X		
TM-7(*)					X		X		
TM-8(**)	7ch Mode				X		X		Via Switch
	8ch Mode					X	X		Via Switch
T8FG 2.4GHz T8FG Super 2.4GHz	7ch Mode			X	X		X		Via Screen Selection
	Multi-ch Mode					X	X		Via Screen Selection
T10C 2.4GHz (with TM-10)	7ch Mode			X	X		X		Via Screen Selection
	10ch Mode					X	X		Via Screen Selection
T10CG 2.4GHz	7ch Mode			X	X		X		Via Screen Selection
	10ch Mode					X	X		Via Screen Selection
TM-14	7ch Mode			X	X		X		Via Screen Selection
	Multi-ch Mode					X	X		Via Screen Selection
T18MZ	FASST	7ch Mode			X	X	X		Via Screen Selection
		Multi-ch Mode					X	X	Via Screen Selection
	FASSTest	18CH Mode						X	Via Screen Selection
		12CH Mode						X	Via Screen Selection
T14SG		7ch Mode			X	X	X		Via Screen Selection
		Multi-ch Mode					X	X	Via Screen Selection
		14CH Mode						X	Via Screen Selection
		12CH Mode						X	Via Screen Selection

(\*)(\*\*) Set the transmitter's mode as "PPM" to use the TM7, TM8.

With selection of "7ch" mode or "8ch" mode via switch, the receivers above listed are available.

(\*\*) With R6014FS, available channel is limited as 8ch since the transmitter's limitation.

With T7U, the R608FS and R6014FS are available with "8ch" mode but available channel is limited as 7ch since the transmitter's limitation.