



LANGUAGES



**XL6S**  
BRUSHLESS POWERED  
SHORT COURSE TRUCK  
PRO ROLLER CHASSIS  
NO ELECTRONICS INCLUDED



## INSTRUCTION MANUAL

Check that you have the latest version of this manual before each use.

Contrôlez avant chaque utilisation de ce manuel si vous en avez la dernière version.

Überprüfen Sie vor jedem Gebrauch dieses Handbuchs, ob Sie die neueste Version haben.

Controleer voor elk gebruik van deze handleiding of u over de laatste versie beschikt.

MANUAL VERSION  
C-00278 Manual - V2



www.corally.com

**WWW.CORALLY.COM**

## TABLE OF CONTENTS

|                                                                                                                                                     |    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Introduction                                                                                                                                        | 3  |
| Use Precautions - Précautions d'emploi - Vorsichtsmaßnahmen bei der Verwendung - Voorzorgsmaatregelen voor gebruik                                  | 4  |
| Kit Content - Contenu du kit - Bausatz Inhalt - Inhoud                                                                                              | 5  |
| Car Explanation - Explication du véhicule - Auto Erläuterung - Auto Uitleg                                                                          | 6  |
| Quick Start Guide - Guide de démarrage rapide - Schnellstart-Anleitung - Snelstartgids                                                              | 7  |
| Gear Ratio - Rapport de transmission - Getriebeübersetzung - Overbrengingsverhouding                                                                | 8  |
| Gear Mesh Adjustment - Réglage de l'engrenage - Einstellen des Zahnrad - Versnelling afstellen                                                      | 9  |
| Shock Absorber Maintenance - Entretien des amortisseurs - Shock Absorber Maintenance - Schokdemper Onderhoud                                        | 10 |
| Shock Absorber Exploded View - Vue éclatée de l'amortisseur - Stoßdämpfer Explosionszeichnung - Schokdemper Exploded View                           | 11 |
| Differential Maintenance - Entretien du différentiel - Wartung des Differentials - Differentieel Onderhoud                                          | 12 |
| Differential Exploded View - Vue éclatée du différentiel - Explosionszeichnung des Differentials - Differentieel Exploded View                      | 14 |
| Front Drive Train Exploded View - Vue éclatée du train avant - Explosionszeichnung des vorderen Antriebsstrangs - Exploded View vooraandrijflijn    | 15 |
| Rear Drive Train Exploded View - Vue éclatée du train arrière - Explosionszeichnung des hinteren Antriebsstrangs - Exploded view achteraandrijflijn | 16 |
| Chassis Exploded View - Vue éclatée du châssis - Explosionszeichnung des Gehäuses - Exploded View chassis                                           | 17 |
| Servo-Saver Exploded View - Vue éclatée du Sauve-Servo - Servo-Saver Explosionszeichnung - Servo-Saver Exploded View                                | 18 |
| Body Exploded View - Vue éclatée de la carrosserie - Explosionszeichnung der Karosserie - Exploded view van het carrosserie                         | 19 |
| Spare Parts - Pièces détachées - Ersatzteile - Onderdelen                                                                                           | 21 |
| Option Parts - Pièces option - Option Teile - Optie Onderdelen                                                                                      | 26 |
| Troubleshooting - Dépannage - Fehlersuche - Problemen oplossen                                                                                      | 26 |
| Screws and Nuts - Visserie et écrous - Schrauben und Muttern - Schroeven en moeren                                                                  | 27 |
| Warranty - Garantie - Garantie - Garantie                                                                                                           | 30 |
| Declaration of Conformity - Déclaration de conformité - Konformitätserklärung - Conformiteitsverklaring                                             | 31 |

Téléchargez le guide de démarrage rapide en Français sur le site • Laden Sie die Kurzanleitung auf Deutsch von der Website herunter • Download de Nederlandse snelstartgids op [www.corally.com](http://www.corally.com)


## DOWNLOAD - TELECHARGER - DOWNLOAD - DOWNLOAD



Download the latest version of this manual and other instruction manuals about :  
**Electronics - LiPo Safety Instructions - Spare parts - Option Parts ...**


### ALL INSTRUCTION MANUALS

Go to :  
<https://corally.com/en/useful-links/downloads-manuals>



### ONE PAGE MANUALS (Step by step manual)

Go to :  
<https://world.corally.com/>



## INTRODUCTION



Thank you for purchasing a Team Corally car. This manual describes the instructions for using the model and the electronic components. You will also find some tips on how to maintain your RC model so that you can enjoy it for years to come. You have purchased one of the most efficient models available on the market that has been designed by a team of professionals. You will also benefit from the best after-sales support. All Team Corally models guarantee a high quality of manufacture and performance that guarantees you a high satisfaction of use and services provided by the Team Corally. Always take the time to read the instructions carefully in order to follow all the procedures to use your RC model safely for you and for other people and property in the area. This will allow you to take full advantage of all the performance of your RC model.

Please also check the website [www.corally.com/Downloads/](http://www.corally.com/Downloads/) to check if you have the latest version of this instruction manual. (Version: see bottom cover of this manual)

If you have any questions about the model and its components, you can send a message to [support@corally.com](mailto:support@corally.com)

We also recommend that you get help from an experienced model maker or your dealer.

You will find all the references of the spare parts on the website [www.corally.com](http://www.corally.com)

### TERM OF USE

The user is responsible for the use of your model. The user assumes all risks associated with the use of the model. This model is not intended for use by children under 14 years of age without the supervision of a responsible adult who is familiar with the dangers of using a RC model. Team Corally / JSP Group Intl bvba, its manufacturers, distributors and resellers cannot control the use and load of the model and therefore cannot be held responsible for any damage to property and damage caused to persons resulting from the use of this product. You must accept these conditions and consider yourself fully responsible for the use of this product. If not, do not use this product.

Due to the continuous development of our products, the exact specifications of the kit may vary. If you have a problem with your new kit, please contact the store where you purchased it, indicating the part number(s).

Team Corally / JSP Group Intl bvba reserves the right to change any specification without notice. All rights reserved.

## READ FIRST

This owner's manual is designed for use with your vehicle and contains the instructions you will need to operate and maintain your vehicle.

- We know you want to start driving immediately after unpacking, but it is very important that you take the time to read this manual carefully, even if you are an experienced R/C driver.
- Read carefully and follow all instructions in this manual. Failure to comply with the instructions will be considered as abuse and/or negligence which may result in the cancellation of the warranty.
- Your vehicle is designed to operate on uneven terrain. However, dust, sand, water and carpet fibres can get into your car's work-spaces and can damage your vehicle if they are not removed quickly. We do not guarantee any warranty on your vehicle against damage caused by external elements such as sand, dirt or water. Users are responsible for the maintenance and safe operation of this vehicle.
- This product is not a toy. It is not suitable for users under 14 years of age, unless they are supervised by adults.
- Never attempt to disassemble electronic components. These have been carefully calibrated at the factory.
- Only improve your car with parts made for your car. If you upgrade performance, replace the entire system (such as the motor, inverter, battery, etc.) so that all components are properly adapted. Any malfunction resulting from a custom modification will void your warranty.
- Before driving your vehicle, please read this manual in its entirety and examine your vehicle and radio control system for any defects.
- For better performance, some adjustments may be necessary.
- This vehicle requires a battery (included in the car or in the packaging). Make sure the vehicle's battery is sufficiently charged before driving, otherwise you may lose control of the vehicle.
- The radio transmitter requires 4 AA batteries (not included)
- Always remove or disconnect the battery from the vehicle to the inverter when not in use.
- Please drive your car in a spacious place. Never drive your car on the street or in traffic. Public places are subject to specific legislation by country, city, municipality, please comply with the legislation for the use of RC models in your region.
- This product is fully assembled in the factory. We accept no liability for damage and/or accidents resulting from custom modifications and/or malfunctions.

## SAFETY PRECAUTIONS

For your safety, always use wear gloves and goggles when assembling and maintaining your model.

Always take all necessary precautions when handling products (silicone oil, grease, thread lock, cyanolyte glue, fuel) for the operation of the model. (Refer to the manufacturer's instructions)

For your safety, to keep the warranty and obtain the best performance, always use original CORALLY genuine parts.

Contains: LEAD (CAS 7439-92-1) ANTIMONY (CAS 7440-36-0)

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

**CAUTION: CANCER HAZARD**

Contains lead, a listed carcinogen. Lead is harmful if ingested. Wash thoroughly after using.



**DO NOT** use product while eating, drinking or smoking.

## USE PRECAUTIONS



Failure to operate your model in a safe and responsible manner may result in injury to yourself, others or damage to property around you.

- Do not use your model on public roads or in areas where you may encounter pedestrians or riders.
- Do not operate in a congested area or in crowds.
- Do not operate in areas where loud noises can disturb others, such as hospitals and residential areas.
- Do not operate your model with obstructed line of sight, at night or near water.
- Your model is radio controlled, it is subject to possible radio interference. Radio interference can cause loss of control of your model. Be careful.
- Take care not to injure yourself while using tools to adjust or upgrade your model.
- Since the model contains small parts, keep out of reach of children while assembling and/or disassembling your model.
- If your model becomes stuck against an object, release the throttle and retrieve it by hand
- Do not continue to apply the throttle when your model is stuck. This may damage the motor and/or ESC/ Receiver unit.
- Turn OFF your model and don't use it if it runs erratically. Please do not use your model again until the problem has been solved.
- Keep the wheels of the model off the ground when checking the operation of the radio equipment.
- When learning to operate your model, go to an area that has no obstacles that can damage your model.
- Before and after each use, check all the screws on the model.
- To maintain the best performance, check that all moving parts move freely.



**Take all necessary precautions before, during and after using your model. You are responsible for the safe assembly, maintenance and use of your model.**

**In case of any questions, contact your local reseller or contact Team Corally support for assistance.**

## LIPO BATTERY SAFETY PRECAUTIONS

- Follow and respect the manufacturer's instructions for use
- It is important to check that your ESC is set to LIPO if you are using a LIPO battery. Failure to comply with this instruction will result in increased battery discharge and may cause fire and damage to persons and property.
- When charging or storing LiPo batteries always use LiPo Safety Bag (Flame retardant).
- Always respect the maximum rate and voltage specified by the battery manufacturer.
- Charge the LIPO battery outdoors or in a ventilated area away from flammable objects and surfaces.
- NEVER leave your LiPo battery unattended while charging.
- If the battery swells during charging, stop charging immediately and disconnect the battery from the charger. Leave the battery outside for a few hours and observe. Then recycle the battery according to the instructions of your country/region. Never dispose of a LIPO battery with domestic waste.
- Before recycling your defective battery, it must be neutralized. Take a plastic container, fill it with water and add a lot of salt until the water becomes opaque. Place the LIPO battery in the water and leave for 24 hours. Check with a voltmeter that the voltage is 0.0V. Then recycle the battery according to local regulations.
- Never charge a damaged or inflated battery.
- Never discharge the battery cells below 3.2V.
- Always use the appropriate balancer/charger when charging your LiPo battery pack.
- When the battery is empty, check the temperature of the battery before charging it. If the battery is very hot, wait until it cools before charging it.
- Never charge a very hot battery as this may cause an explosion or fire.
- When the battery is empty, recharge it immediately. Do not store an empty battery, the battery will continue to discharge, it will fall below the minimum voltage and become unusable.



This product is in accordance with Directive 2014/53/EC and can be used in following countries

AT - BE - CY - CZ - HR - DK - EE - FI - FR - DE - GR - HU - IE - IT - LV - LT - LU - MT - NL - PL - PT - SK - SI - ES - SE - GB - IS - LI - NO - CH - BG - RO - TR

This product complies with part 15 of the FCC Rules. For our global distributors and authorised resellers, please refer to [www.corally.com](http://www.corally.com)



## TECHNICAL SPECIFICATIONS

|                            |           |                     |
|----------------------------|-----------|---------------------|
| Length :                   | . . . . . | .620mm ( 24.4" in ) |
| Width :                    | . . . . . | . 315mm (12.4" in ) |
| Height :                   | . . . . . | . 235mm ( 9.2" in ) |
| Wheelbase :                | . . . . . | . 388mm (15.3" in ) |
| Weight (without Battery) : | . . . . . | . 5250g ( 185 oz )  |
| Ground Clearance           | . . . . . | . 70mm ( 2.75" )    |

## KIT CONTENT



2.4 GHz Digital Transmitter



RTR Model - Electronics included



Manuals



**KURON 825**  
Sensorless Brushless Motor  
4-Pole • 2050KV • 4-6S



**TOROX 185 Sensorless ESC**  
• Waterproof • 150A Cont. Current  
• 2-6S LiPo • HV BEC




**CRHV-7225**  
• HV Digital Servo • Metal Gears  
• Torque 25Kg/cm

## REQUIRED FOR OPERATION (Not included)



4x AA Batteries  
for the Transmitter



LiPo - Min. capacity of 4000mAh  
4S - 14.8V LiPo Battery - Hard case  
6S - 22.2V LiPo Battery - Hard case



C-51025 - ULTRA-X 80 Charger



C-16185 - Hex Tool Set  
1.5 / 2.0 / 2.5 / 3.0 mm

## Team Corally - Energy Pack



**C-47146-03-05 - Team Corally - Energy Pack**  
1x Lipo 50C - 6700mAh - 4S - XT-90 - Hard Case  
1x Ultra-X 80 - 1-6S AC/DC Charger  
1x Lipo Safety Bag  
1x Charge-Balance Lead




**C-47146-03-05 - Team Corally - Energy Pack**  
1x Lipo 50C - 6700mAh - 4S - XT-90 - Hard Case  
1x Racer 50 - 2-4S AC Charger  
1x Lipo Safety Bag  
1x Charge-Balance Lead

Select other compositions from  
our ENERGY PACKS here



## CAR EXPLANATION








## QUICK START GUIDE • QUICK START GUIDE

### READ THE INSTRUCTIONS



- Lisez les instructions
- Lesen Sie die Anleitung
- Lees de instructies

### CHARGE THE BATTERY




- Chargez la batterie
- Laden Sie den Akku
- De batterij opladen

### INSTALL 4x AA BATTERY - 1.5V




- Respect the polarity
- Respectez la polarité
- Beachten Sie die Polarität
- Respekteer de polariteit
- Installez les piles dans l'émetteur
- Setzen Sie die Batterien in den Sender ein
- Plaats de batterijen in de zender

### MAKE SURE THAT ALL SCREWS AND NUTS ARE TIGHTENED PROPERLY.



- Vérifiez le serrage des vis et écrous
- Überprüfen Sie die Schrauben und Muttern auf festen Sitz
- Controleer de vastheid van de schroeven en moeren

### INSTALL THE BATTERY




- Installez la batterie chargée
- Setzen Sie den geladenen Akku ein
- Installeer de opgeladen batterij

### TURN ON THE TRANSMITTER (Always First)




- Allumez l'émetteur (Toujours en premier)
- Schalten Sie den Sender ein (Immer zuerst)
- Zet de zender aan (altijd eerst)

### CONNECT THE BATTERY TO THE ESC SWITCH ON THE ESC



- Connectez la batterie au variateur et allumez-le
- Schließen Sie den Akku an den Regler an und schalten Sie ihn ein
- Sluit de accu aan op de regelaar en schakel deze in

### CHECK THE FUNCTIONS



- Contrôlez les fonctions
- Kontrollieren Sie die Funktionen
- Controle van de functies


### CHECK THE RADIO SYSTEM RANGE



Move away from the max. distance you will drive the vehicle.  
Check that the vehicle responds properly to the controls.  
If not, reduce the distance or change the driving location.


- Contrôlez la portée de l'émetteur
- Überprüfen Sie die Reichweite des Senders
- Controleer het bereik van de zender

### DRIVE SLOWLY TO BEGIN



- Pour débuter placez le sélecteur de vitesse sur 1
- Um zu beginnen, stellen Sie den Geschwindigkeitswahlschalter auf 1
- Zet om te beginnen de snelheidskeuzeknop op 1

### WHEN FINISHING



- Après, débranchez la batterie et rechargez-la immédiatement.
- Trennen Sie den Akku ab und laden Sie ihn sofort wieder auf.
- Ontkoppel dan de batterij en laad deze onmiddellijk op.

### CLEAN AND MAINTAIN YOUR VEHICLE




- Nettoyez et entretenez votre voiture !
- Reinigen und pflegen Sie Ihr Auto!
- Reinigen en onderhoud uw auto!

## MOTOR PINION MOD1.0 - PIGNON MOTEUR MOD1.0 - MOTORRITZEL MOD1.0 - MOTOR PINION MOD1.0



High-performance pinions gear, manufactured from special steel for toughness and durability with precise tolerances and assures unparalleled concentricity. Created on a special gear machine, all pinions feature ultra-precise tooth shaping and ultra-true running for vibration-free operation. Each pinion is marked with the tooth number for easy and quick identification. Fits all cars with MOD1 gears (1/8 Scale)



Pignons Haute Performance, fabriqué en acier spécial avec des tolérances précises pour garantir solidité, longévité et concentricité. Tous les pignons présentent une forme de dent ultra-précise pour un fonctionnement sans vibrations. Chaque pignon est marqué du nombre de dents pour une identification facile et rapide. Convient à toutes les voitures avec des transmissions MOD1 (Echelle 1/8)



Hochleistungs-Ritzel, hergestellt aus Spezialstahl mit präzisen Toleranzen, um Festigkeit, Haltbarkeit und Rundlauf zu gewährleisten. Alle Ritzel haben eine ultrapräzise Zahnform für einen vibrationsfreien Betrieb. Jedes Kettenrad ist zur schnellen und einfachen Identifizierung mit der Anzahl der Zähne gekennzeichnet. Passend für alle Fahrzeuge mit MOD1-Getriebe (Maßstab 1/8)



High-performance tandwiel, geproduceerd van speciaal staal met nauwkeurige toleranties om sterkte, duurzaamheid en concentriciteit te garanderen. Alle kettingwielen hebben een ultra-precieze tandvorm voor een trillingsvrije werking. Elk tandwiel is gemarkeerd met het aantal tanden voor een snelle en eenvoudige identificatie. Past op alle auto's met MOD1 versnellingen (1/8 Schaal)

### With Spur Gear 52T - Gear Ratio 3.31

Avec couronne 52D - Rapport de démultiplication 3.31 - Mit Hauptzahnrad 52Z - Gear Ratio 3.31 - Met tandwiel 52T - Gear Ratio 3.31

| Main Gear | Voltage | Pinion 13T |     | Pinion 14T |     | Pinion 15T |     | Pinion 16T |     | Pinion 17T |     | Pinion 18T |     |
|-----------|---------|------------|-----|------------|-----|------------|-----|------------|-----|------------|-----|------------|-----|
|           |         | Km/h       | MPH | Km/h       | MPH | Km/h       | MPH | Km/h       | MPH | Km/h       | MPH | Km/h       | MPH |
|           |         | 13,23      |     | 12,29      |     | 11,47      |     | 10,75      |     | 10,12      |     | 9,56       |     |
| 52        | 4S      | 56         | 35  | 60         | 37  | 65         | 40  | 69         | 43  | 73         | 45  | 78         | 48  |
| 52        | 6S      | 84         | 52  | 91         | 57  | 97         | 60  | 104        | 65  | 110        | 68  | 116        | 72  |

Factory fitted

OK

Usable but not recommended

Not recommended, at your own risk

+TORQUE

+SPEED

Note: The speed indicated in the table is a theoretical speed for information purposes. The real speed varies according to the type of terrain, electronic equipment, atmospheric conditions, type of tyre and its diameter and other driving parameters.

Note: La vitesse indiquée dans le tableau est une vitesse théorique à titre indicatif. La vitesse réelle varie en fonction du type de terrain, de l'équipement électronique, des conditions atmosphériques, du type de pneu et son diamètre et d'autres paramètres de conduite.

Bemerkung: Die in der Tabelle angegebene Geschwindigkeit ist eine theoretische Geschwindigkeit, die nur als Referenz dient. Die tatsächliche Geschwindigkeit hängt von der Art des Geländes, der elektronischen Ausrüstung, den Wetterbedingungen, des Reifentyps und seines Durchmessers und anderen Fahrparametern ab.

Nota: De in de tabel aangegeven snelheid is een theoretische snelheid, uitsluitend ter referentie. De werkelijke snelheid varieert afhankelijk van het soort terrein, de elektronische apparatuur, de weersomstandigheden, het type band en zijn diameter en andere rijparameters.

### OPTION M1.0 Pinion - Hardened Steel - for Shaft Dia. 5mm

C-72711 - Pinion 11 Teeth

C-72712 - Pinion 12 Teeth

C-72713 - Pinion 13 Teeth

C-72714 - Pinion 14 Teeth

C-72715 - Pinion 15 Teeth

C-72716 - Pinion 16 Teeth





## GEAR MESH ADJUSTMENT - AJUSTEMENT DE L'ENGRENAGE - GETRIEBEVERSTELLUNG - TANDWIELAFSTELLING



If the gear mesh is not correct, you wear out the spur gear prematurely, the transmission will make noise, give unnecessary load on the motor (higher consumption, heating of the transmission).





Si l'espace entre le pignon et la couronne n'est pas correct, la couronne dentée s'use prématurément, la transmission fait du bruit et le moteur est inutilement sollicité (consommation plus élevée, échauffement de la transmission).



Wenn der Abstand zwischen Ritzel und Tellerrad nicht stimmt, verschleißt das Zahnrad vorzeitig, das Getriebe macht Geräusche und der Motor wird unnötig belastet (höherer Verbrauch, Erwärmung des Getriebes).



Als de afstand tussen het tandwiel en de recht tandwiel niet correct is, slijt de recht tandwiel voortijdig, maakt de transmissie lawaai en wordt de motor onnodig belast (hoger verbruik, verhitting van de transmissie).



### 1. Loosen the screws.


*Desserrez les vis.  
Lösen Sie die Schrauben.  
Draai de schroeven los.*

### 2. Insert the paper strip.

*Insérez la bande de papier.  
Legen Sie den Papierstreifen ein.  
Plaats de papierstrook.*

### 3. Push the motor against the spur gear.

*Poussez le moteur contre la couronne dentée.  
Schieben Sie den Motor gegen das Zahnrad.  
Duw de motor tegen het recht tandwiel.*



### 4. Turn the spur gear to run the paper through the teeth.

**Stop when the paper is in the middle.  
Make sure that the motor pinion is against the spur gear.**

*Tournez la couronne dentée pour faire passer le papier entre les dents.  
Arrêtez lorsque le papier est au milieu.  
Assurez-vous que le pignon du moteur est contre la couronne dentée.*

Drehen Sie das Hauptzahnrad, um das Papier durch die Zähne zu führen.  
Halten Sie an, wenn sich das Papier in der Mitte befindet.  
Achten Sie darauf, dass das Motorritzel am Hauptzahnrad anliegt.

*Draai aan het rechte tandwiel om het papier door de tanden te laten lopen.  
Stop wanneer het papier in het midden is.  
Zorg ervoor dat het motortandwiel tegen het rechte tandwiel staat.*

### 5. Maintain and tighten the fixing screws.



*Maintenez et serrez les vis de fixation.  
Halten Sie die Befestigungsschrauben fest und ziehen Sie sie an.  
De bevestigingsschroeven aanhouden en vastdraaien.*

It may be necessary to replace the silicone oil in the shock absorbers every 40 runs (depends on how you drive and the type of terrain you drive on).

Il peut être nécessaire de remplacer l'huile silicone des amortisseurs toutes les 40 courses (cela dépend de votre conduite et du type de terrain sur lequel vous roulez).

Es kann notwendig sein, das Silikonöl in den Stoßdämpfern alle 40 Fahrten zu wechseln (abhängig von Ihrer Fahrweise und dem Gelände, auf dem Sie fahren).

Het kan nodig zijn de siliconenolie in de schokdempers om de 40 ritten te vervangen (afhankelijk van uw rijstijl en het soort terrein waarop u rijdt).



ALWAYS USE SILICONE OIL, NEVER USE ANY OTHER TYPES OF OIL.

**FILL**

**2**

**1**

**MOVE UP**

**3-4x**

**WAIT**

**5min**

**TIGHTEN 50%**

**MOVE UP**

**SLOWLY**

**TIGHTEN FULLY**

- Fill the shock with silicone oil.
- Remplissez l'amortisseur avec de l'huile de silicone.
- Füllen Sie den Dämpfer mit Silikonöl.
- Vul de schokdemper met siliconenolie.

- Move the piston up&down (3-4x) to release the air bubbles in the silicone oil.
- Déplacez le piston de haut en bas (3-4x) pour libérer les bulles d'air.
- Bewegen Sie den Kolben nach oben&unten (3-4x), um die Luftblasen abzulassen.
- Beweeg de zuiger op en neer (3-4x) om de luchtbel-len te laten ontsnappen.

- Pull the Shock shaft down and wait until the bubbles rise to the surface.
- Tirez la tige d'amortisseur vers le bas et attendez que les bulles remontent à la surface.
- Ziehen Sie die Schockwelle nach unten und warten Sie, bis die Blasen an die Oberfläche steigen.
- Trek de Schokas naar beneden en wacht tot de luchtbel-len naar de oppervlakte stijgen.


- Screw in the shock absorber cap at 50%.
- Vissez le bouchon d'amortisseur à 50%.
- Schrauben Sie die Stoßdämpferkappe zu 50 % ein.
- Schroef de dop van de schokdemper op 50%.

- Gently move the piston in upper position, the oil excess will flow out.
- Déplacez doucement le piston en position haute, l'excédent d'huile s'écoulera.
- Bewegen Sie den Kolben vorsichtig in die obere Position, das überschüssige Öl fließt dann heraus.
- Beweeg de piston langzaam in de bovenste positie, de overtollige olie zal eruit stromen.

- Now tighten the cap fully but not too much otherwise the membrane will be deformed.
- Maintenant, serrez le bouchon à fond, mais pas trop, sinon la membrane sera déformée.
- Ziehen Sie nun die Kappe vollständig, aber nicht zu fest an, da sonst die Membran verformt wird.
- Draai nu de dop helemaal vast, maar niet te vast, anders wordt het membraan vervormd.

|           | FRONT        |                | REAR         |                | SHOCK PISTON   |
|-----------|--------------|----------------|--------------|----------------|----------------|
|           | SILICONE OIL | SPRING TENSION | SILICONE OIL | SPRING TENSION |                |
| TRACK USE | 450CPS       | 4mm            | 400CPS       | 0mm            | 6 Holes Ø1.3mm |
| OFF-ROAD  | 600CPS       | 4mm            | 500CPS       | 0mm            | 6 Holes Ø1.3mm |
| FACTORY   | 1000CPS      |                | 1000CPS      |                | 6 Holes Ø1.3mm |

- Do not overtighten the Shock Cap to prevent deformation of the silicone Shock Bladder.
- Ne serrez pas trop le capuchon de l'amortisseur pour éviter la déformation de la membrane en silicone.
- Ziehen Sie die Dämpferabdeckung nicht zu fest an, um eine Verformung der Silikonmembran zu vermeiden.
- Draai de schokkap niet te strak aan om vervorming van het siliconenmembraan te voorkomen.




**APPLY SILICONE OIL**

- Appliquez de l'huile silicone
- Silikonöl auftragen
- Breng siliconenolie aan



**C-00180-768 Shock Piston (8pcs)**  
Shock Piston - **6 Holes 1.4**  
Shock Piston - **8 Holes 1.2** (Factory installed)




- Place all small parts on a screwdriver (Ø3mm) and push them into the shock body. All parts will be properly aligned.

- Placez toutes les petites pièces sur un tournevis (Ø3mm) et poussez-les dans le corps de l'amortisseur. Toutes les pièces seront correctement alignées.

- Setzen Sie alle Kleinteile auf einen Schraubendreher (Ø3mm) und drücken Sie sie in den Dämpferkörper. Alle Teile werden richtig ausgerichtet.

- Plaats alle kleine onderdelen op een schroevendraaier (Ø3mm) en duw ze in de behuizing van de schokdemper. Alle onderdelen zullen goed uitgelijnd zijn.

## OPTION



| REF         |              | TYPE   | POSITION | THICKNESS | LENGTH     |
|-------------|--------------|--------|----------|-----------|------------|
| C-00180-286 | Shock Spring | SOFT   | FR&RE    | 1.4mm     | L: 95-97mm |
| C-00180-287 | Shock Spring | MEDIUM | FR&RE    | 1.6mm     | L: 95-97mm |
| C-00180-288 | Shock Spring | HARD   | FR&RE    | 1.8mm     | L: 95-97mm |





It may be necessary to replace the silicone oil every 50 runs (depends on how you drive and the type of terrain you drive on).  
To remove the FR&RE differentials, follow the steps below.




Il peut être nécessaire de remplacer l'huile silicone toutes les 50 courses (cela dépend de votre conduite et du type de terrain sur lequel vous roulez).  
Pour extraire les différentiels AV et AR, suivez les étapes indiquées ci-dessous.




Es kann notwendig sein, das Silikonöl alle 50 Fahrten zu wechseln (abhängig von Ihrer Fahrweise und dem Gelände, auf dem Sie fahren).  
Um das Vorder- und Hinterachsdifferential herauszuziehen, befolgen Sie die unten beschriebenen Schritte.



Het kan nodig zijn de siliconenolie om de 50 ritten te vervangen (afhankelijk van uw rijstijl en het soort terrein waarop u rijdt).  
Volg de onderstaande stappen om het voor- en achterdifferentieel te verwijderen.





**FRONT**  
AVANT • VORNE • VOOR



**REAR**  
ARRIERE • HINTEN • ACHTER

# CENTRE

CENTRE • MITTE • MIDDEN



**Perform the same maintenance operation for the Front, Centre and Rear differentials.**

*Effectuez la même opération d'entretien pour les différentiels avant, central et arrière.*

Führen Sie die gleichen Wartungsarbeiten für die vorderen, mittleren und hinteren Differentiale durch.


Voer dezelfde onderhoudswerkzaamheden uit voor de differentiëlen vooraan, in het midden en achteraan.

[www.corally.com/Chemicals/Silicone-Oils/](http://www.corally.com/Chemicals/Silicone-Oils/)


|          | FRONT DIFF | CENTRE DIFF | REAR DIFF |
|----------|------------|-------------|-----------|
| OFF-ROAD | 10.000CPS  | 30.000CPS   | 7500CPS   |
| BASHING  | 20.000CPS  | 100.000CPS  | 10.000CPS |
| FACTORY  | 20.000CPS  | 100.000CPS  | 10.000CPS |




# FRONT & REAR DIFFERENTIAL - DIFFÉRENTIEL AVANT ET ARRIÈRE - DIFFERENTIAL VORNE UND HINTEN - VOOR & ACHTER DIFFERENTIEEL



# CENTRE DIFFERENTIAL - DIFFÉRENTIEL CENTRAL - ZENTRALDIFFERENTIAL - CentreDIFFERENTIEEL








- 8 M3x8mm  
#C-3003-30-08
- 10 M3x10mm  
#C-3003-30-10
- 12 M3x12mm  
#C-3003-30-12
- 14 M3x14mm  
#C-3003-30-14
- 16 M3x16mm  
#C-3003-30-16
- 20 M3x20mm  
#C-3003-30-20



- 8 M3x8mm  
#C-3002-30-08
- 10 M3x10mm  
#C-3002-30-10
- 12 M3x12mm  
#C-3002-30-12
- 16 M4x16mm  
#C-3002-40-16
- 20 M4x20mm  
#C-3002-40-20

**OPTION**


Aluminium 7075  
Hard Anodised







Fit FRONT  
or REAR


**C-00180-854**  
Gearbox Case Set - Swiss Made 7075 T6 - Black

**Front Shock-tower - Screws description**











| HEX BUTTON HEAD SCREWS<br>DIN 7380 - STEEL - 10 PCS |
|-----------------------------------------------------|
| 4 M3x4mm<br>#C-3003-30-04                           |
| 6 M3x6mm<br>#C-3003-30-06                           |
| 8 M3x8mm<br>#C-3003-30-08                           |
| 10 M3x10mm<br>#C-3003-30-10                         |
| 12 M3x12mm<br>#C-3003-30-12                         |
| 16 M3x16mm<br>#C-3003-30-16                         |
| 20 M3x20mm<br>#C-3003-30-20                         |
| 25 M3x25mm<br>#C-3003-30-25                         |
| 35 M3x35mm<br>#C-3003-30-35                         |
| 25 M4x25mm<br>#C-3003-40-25                         |

| HEX FLAT HEAD SCREWS<br>DIN 7991 - STEEL - 10 PCS |
|---------------------------------------------------|
| 6 M3x8mm<br>#C-3002-30-08                         |
| 8 M3x8mm<br>#C-3002-30-08                         |
| 10 M3x10mm<br>#C-3002-30-10                       |
| 12 M3x12mm<br>#C-3002-30-12                       |
| 14 M3x14mm<br>#C-3002-30-14                       |
| 18 M3x18mm<br>#C-3002-30-18                       |
| 16 M4x16mm<br>#C-3002-40-16                       |
| 20 M4x20mm<br>#C-3002-40-20                       |




## CHASSIS - SCREWS DESCRIPTION - VISSERIE CHÂSSIS - SCHRAUBEN - SCHROEVEN

- M3x8mm DIN7991  
#C-3002-30-08
- M3x12mm DIN7991  
#C-3002-30-12
- M4x10mm DIN7991  
#C-3002-40-10
- M4x12mm DIN7991  
#C-3002-40-12
- M4x14mm DIN7991  
#C-3002-40-14
- M4x16mm DIN7991  
#C-3002-40-16
- M4x20mm DIN7991  
#C-3002-40-20








# BODY EXPLODED VIEW







| <br>HEX BUTTON HEAD SCREWS<br>DIN 7380 - STEEL - 10 PCS |                          |
|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| 8                                                                                                                                         | M3x8mm<br>#C-3003-30-8   |
| 10                                                                                                                                        | M3x10mm<br>#C-3003-30-10 |
| 12                                                                                                                                        | M3x12mm<br>#C-3003-30-12 |
| 16                                                                                                                                        | M3x16mm<br>#C-3003-30-16 |



C-00180-004-1  
Battery Strap - Hook & Loop  
- 2 pcs



C-00180-008  
Composite Rear Upright - 1 Pc



C-00180-009-1  
HD Steering Block - Pillow Ball  
Cup (2) - Front - 1 Set




C-00180-013  
Servo Mount - Receiver Box -  
Composite - 1 Set



C-00180-018  
Centre Diff Bulkhead - Compos-  
ite - 1 Set



C-00180-023  
Motor Mount Centre Diff Insert -  
Composite - 1 Pc



C-00180-029  
Shock Spring Cup - Composite  
- 4 pcs




C-00180-033  
Bumper - Front - Rear - Com-  
posite - 1 set



C-00180-036  
Steering Bellcrank - Parts A-B-C  
- Composite - 1 Set



C-00180-044  
Ball Joint 6mm - Composite -  
2 pcs



C-00180-055  
Suspension Arm Shim - Com-  
posite - 1 Set



C-00180-089  
Anti-Roll Bar Ball Cups - Com-  
posite - 4 pcs




C-00180-098  
Diff Case - FR-RE - Composite  
- 1 Pc



C-00180-109  
Caster Clips Set - 1 to 4.5mm  
- 1 Set



C-00180-117  
Pivot Ball Adjusting Nut - Alu-  
minium - 4 pcs



C-00180-122  
Pin 2.5x17mm - Steel - 10 pcs



C-00180-123  
Pivot Ball - Steel - 4 pcs



C-00180-127  
Hinge Pin - Outer - Steel - 2 pcs



C-00180-129  
Turnbuckle - M3 - 35mm -  
Steel - 2 pcs



C-00180-145  
Servo Saver Shaft w/ Nut -  
Aluminium - 1 Pc



C-00180-147  
Servo Saver Post - Steel - 2 pcs



C-00180-148  
Shock Screw - Steel - 4 pcs



C-00180-149  
Ball - 5.8mm - Steel - 4 pcs



C-00180-150  
Ball Shouldered - 6.8mm - Steel  
- 4 pcs




C-00180-170  
Ball - 6.8mm - Steel - 2 pcs



C-00180-171  
Threaded Ball - 6mm - Steel -  
2 pcs



C-00180-177  
Motor Mount - Aluminium - 1  
Pc



C-00180-187  
O-Ring - Silicone - 12x1mm  
- 2 pcs



C-00180-195  
Anti-Roll Bar - 2.6mm - Front  
- 1 Pc



C-00180-206  
Steering Rack Bushing - Steel  
- 2 pcs



C-00180-207  
Steering Block Arms - Alumi-  
nium - 2 pcs




C-00180-216  
Servo Saver Spring - 1 Pc



C-00180-220  
Ball End 5.8mm - for Anti Roll  
Bar - Steel - 4 pcs



C-00180-231  
Collar - for Anti-roll Bar - Alu-  
minium - 1 Pc




C-00180-246  
Anti-Roll Bar - Rear - 2.6mm  
- 1 Pc



C-00180-293  
Ball 6.8mm - Steel - 4 pcs




C-00180-305  
Centre Roll Cage Pin - Steel  
- 2 pcs



C-00180-322  
Susp. Arm Pivot Pin - Lower Inner  
- Fr/Re - Steel - 68mm - 2 Pcs



C-00180-329-B  
Wheel Hex Adapter - Wide RTR  
- Aluminium - 2 pcs



C-00180-360  
CVD Drive Shaft - Short - Front  
- 1 Pc




C-00180-369-2  
Dogbones - 94mm - 90 Deg.  
offset - Steel - 2 Pcs



C-00180-370-X  
PRO Drive Axle - Short - Rear -  
Swiss Spring Steel - 2 Pcs



C-00180-372  
Servo Arm - Aluminium - 1 Pc



C-00180-531  
HDA Suspension Arm Insert -  
Inner - Aluminium - Red - 2 pcs



C-00180-532  
HDA Susp. Arm Insert - Outer -  
Spacer 1.5mm - Alum - Red - 2 pcs



C-00180-552  
Rear Bumper - Composite. -  
1 Pc



C-00180-555-1  
HD Steering Links - B-1/HDA-5  
- 77mm - 2 Pcs




C-00180-556-1  
HD Camber Links - B-1/HDA-5  
- 93mm - 2 Pcs



C-00180-562  
Centre Diff Support Spacer -  
4mm - Composite - 1 Pc



C-00180-605  
Motor Bulkhead - Aluminium  
- 1 Pc



C-00180-614  
Body Clip Retainer w/ Body clip  
- Black - 6 pcs




C-00180-615  
Battery Tray - Large - Compos-  
ite - 1 set




C-00180-640  
Centre Diff Plate - for Chassis  
Tube - Composite - 1 Pc



C-00180-658  
Shock absorber cover - Com-  
posite - 4 pcs



C-00180-660  
Switch Holder TOROX 185-135  
- Composite - 1 set



C-00180-716  
Centre Roll Cage Mount - Com-  
posite - 1 Set



C-00180-722  
Spur Gear Cover - Composite  
- 1 Pc



C-00180-831  
Steering Rack - Dual Stiffener -  
Aluminium - 1 Pc



C-00180-871  
Suspension Arm Mount HD - RE-FR  
- 8mm - Aluminium - Black - 1 Pc



C-00180-872  
Suspension Arm Mount HD - FR-RE  
- 8mm - Aluminium - Black - 1 Pc




C-00180-873  
Suspension Arm Mount HD - RE-RE  
- 8mm - Aluminium - Black - 1 Pc



C-00180-874  
Suspension Arm Mount HD - FR-FR  
- 8mm - Aluminium - Black - 1 Pc



C-00180-891  
Hinge Pin - Front Upper Arm -  
Steel - 2 pcs



C-00180-907  
Arm Holder Inserts - Composite  
- 0°, 1° - Set 8 pcs




C-00180-934  
Suspension Arm HDA-5 - Lower  
- Rear - 1 Pc



C-00180-935  
Suspension Arm HDA-5 - Lower -  
Front - 1 Pc




C-00180-936  
Suspension Arm HDA-5 - Upper  
- Front - Black - 1 Pc



C-00180-944  
Chassis - MT23 - Aluminium  
- 1 Pc




C-00180-945  
Side Guards - MT23 - Left-  
Right - Composite - 1 Set



C-00180-951  
Chassis Brace Tube Cover -  
Front - Rear - 1 Set







C-00180-952  
Chassis Brace - MT23 - Rear - Composite - 1 Pc



C-00180-953  
Chassis Tube - MT23 - Front - Rear - Aluminium - Black - 1 Set




C-00180-954  
Centre Drive Shaft - Rear - Steel - 141,5mm - 1 Pc




C-00180-957  
Chassis Brace - MT23 - Front - Composite - 1 Pc



C-00180-959  
Chassis Tube Ends - MT23 - Composite - 2 pcs



C-00180-962  
Gear Box Cover - Composite - 1 Set



C-00180-963  
Centre Drive Shaft - Front - Steel - 115,5mm - 1 Pc



C-00180-964  
Steering Rack - MT23 - 7075 - 3mm - Black - 1 Pc



C-00180-1117-B  
Wheel Nut - Serrated - Aluminium - Black - 4 Pcs



C-00180-1233  
Shock Tower - Front - 5mm - Aluminium - Black - 1 Pc




C-00180-1234  
Shock Tower - Front - 5mm - Aluminium - Black - 1 Pc



C-00180-1235  
Bumper Set - Front - 1 Set



C-00180-1236  
Bumper Set - Rear - 1 Set



C-00180-1244  
Body Post - Body Holder - 4 Pcs



C-00180-1245  
Side Guard - Body Bars - L/R - 1 Pair



C-00180-1247  
Body Post Holder L/R - Shock Tower Covers FR/RE - 1 Set



C-00180-1250  
SC Tires - Mudclaws - Glued on Black SC Rims - 1 Pair




C-00180-1253  
Mud Guards - L/R - 1 Pair




C-00180-1297  
Team Corally - Side Guards - Left-Right - 1 Set




C-00180-1299  
Roof Rack - L/R - 1 Pair



C-00180-1301  
Roll Cage - A-Parts - 1 Set



C-00180-1305  
Roll Cage - B-Parts - L/R - 1 Pair



C-00180-1252  
Polycarbonate Body - SHIROI - Clear - Cut - Decals - 1 Pc



C-00180-1338  
Polycarbonate Interior for SHIROI - Painted - Cut




C-00180-1252-1  
Polycarbonate Body - SHIROI - RED - Painted & Cut - Decals



C-00180-1252-2  
Polycarbonate Body - SHIROI - BLUE - Painted & Cut - Decals



C-00180-1252-3  
Polycarbonate Body - SHIROI - GREEN - Painted & Cut - Decals



C-00180-1252-4  
Body Decal Sheet - SHIROI - 1 Pc



C-72713  
M1,0 Pinion - Hardened Steel - 13 Teeth - Shaft Dia. 5mm




C-3611-3-06-10-03  
Ball Bearing - Abec 3 - 6x10x3 - 2 Pcs



C-3611-3-08-16-05  
Ball Bearing - Abec 3 - 8x16x5 - 2 Pcs



## FRONT & REAR DIFFERENTIAL - SPARE PARTS




C-3611-3-08-16-05  
Ball Bearing - Abec 3 - 8x16x5  
- 2 Pcs



C-00180-178  
Diff. Bevel Gear 43T - Steel -  
1 Pc



C-00180-156  
Bevel Pinion 13T - Steel - 1 Pc



C-00180-179  
Planetary Diff. Gears - Steel -  
1 Set




C-00180-184  
Gear Diff. Pin - Steel - 2 pcs




C-00180-205  
Diff. Outdrive Pin - 2x11,8mm -  
Steel - 4 pcs



C-00180-098  
Diff Case - FR-RE - Composite  
- 1 Pc



C-00180-182  
O-Ring - Silicone - 5x8mm -  
5 pcs



C-00180-183-2  
Diff. Gasket - 30x0.3mm - Front  
and Rear Diff - 4 Pcs



C-00180-155-X  
PRO Pinion Outdrive Cup -  
Swiss Spring Steel - 2 pcs




C-00180-153-X  
PRO Diff. Outdrive Cup - Swiss  
Spring Steel - 2 pcs

## CENTRE DIFFERENTIAL - SPARE PARTS



C-00180-154-X  
PRO Centre Diff. Outdrive Cup -  
Swiss Spring Steel - 2 pcs




For use with Diff Pin C-00180-684

C-00180-686  
Diff Case - Centre - Aluminium.  
- 1 Pc



C-00180-607  
Spur Gear 52T - Steel - 1 Pc



C-00180-179  
Planetary Diff. Gears - Steel -  
1 Set




For use with C-00180-686

C-00180-684  
Gear Diff Pin - 3.5x29.8mm -  
for C-00180-686 - Steel - 4 pcs



C-00180-183-1  
Central Diff. Gasket 35mm - 4  
pcs




C-00180-182  
O-Ring - Silicone - 5x8mm -  
5 pcs



C-3611-3-08-16-05  
Ball Bearing - Abec 3 - 8x16x5  
- 2 Pcs

## SHOCK ABSORBER - SPARE PARTS



C-00180-658  
Shock Cap Cover - RTR - Composite - 2 pcs



C-00180-133  
Shock Cap - Aluminium - Hard Anodised - 2 pcs



C-00180-189  
Shock Bladders - Silicone - 4 pcs



C-00180-768  
Shock Piston Heavy Duty - 4mm thick - 8x1.2 + 6x1.4 - 1 Set



C-00180-190  
Shock Washer - 2.5x6x0.5mm - Steel - 10 pcs



C-00180-164  
Shock Shaft - 66mm - Rear - Steel - 2 pcs



C-00180-134  
Shock Body - Rear - Aluminium - Hard Anodised - 1 Pc



C-00180-288  
Shock Spring - Hard - Rear - 2 pcs



C-00180-191  
O-Ring - Silicone - 9x12mm - 5 pcs



C-00180-136  
Shock Collar - Aluminium - Hard Anodised - 2 pcs



C-00180-078  
Shock Body Insert - Washer - Composite - 1 set



C-00180-188  
O-Ring - Silicone - 4x8mm - 5 pcs



C-00180-138  
Shock Cap - Lower - Composite - 2 pcs



C-00180-192  
O-Ring - Silicone - 16.2x19.8mm - 5 pcs



C-00180-029  
Shock Spring Cup - Composite - 4 pcs



C-00180-770  
HD Shock End - Short - Composite - 4 pcs



C-3101-25-6  
Steel Nylstop Nut M2.5 - Black Coated - 10 pcs

## ELECTRONICS - COMPOSANTS ÉLECTRONIQUES • ELEKTRONIKTEILE • ELEKTRONICA-ONDERDELEN



C-54055  
Brushless Motor - Kuron 825 - 4-Pole - 2050 KV - Sensorless



C-54011  
Speed Controller - TOROX 185 - Brushless - 2-6S



C-52022  
Digital Servo - CRHV-7225-MG - High Voltage - Metal Gear



CHECK THE AVAILABILITY OF SPARE PARTS ON THE WEBSITE [WWW.CORALLY.COM](http://WWW.CORALLY.COM)

Visualisez la disponibilité des pièces de rechange sur le site web [www.corally.com](http://www.corally.com)  
Sehen Sie sich die Verfügbarkeit von Ersatzteilen auf der Website [www.corally.com](http://www.corally.com) an.  
Controleer de beschikbaarheid van reserveonderdelen op de website [www.corally.com](http://www.corally.com)



## OPTION PARTS - PIÈCES D'OPTION - OPTIONSTEILE - OPTIES



C-00180-903  
HD Steering Ball Joint - Composite - 1 set



C-00180-143-2  
Turnbuckle - M5 - 92mm - Spring Steel - 2 pcs



C-00180-899  
HD Rear Camber Ball Joint - Outer - Inner - 1 set



C-00180-316  
Shock Cap - Lower - Aluminium - 2 pcs



**Aluminium 7075  
Hard Anodised**  
C-00180-410  
Xtreme Diff Case - 30mm - FR / RE - Made in Italy - 1 Pc



**Aluminium 7075  
Hard Anodised**  
C-00180-854  
Gearbox Case Set - Swiss Made 7075 T6 - Black - Set



C-00180-835  
Centre Roll Cage Foam - Thickness 25mm



**Aluminium 7075  
Hard Anodised**  
C-00180-1211  
Chassis - Swiss Made 7075 T6 - 3mm - Hard Anodised - Black  
**Made in Italy**




C-00180-134-1  
Shock Absorber "Ready Build" - 600 Cps Silicone Oil - Rear - 1 Pc



C-49164-X  
Sport Racing 50C - 4500Mah - 6S - 22,2V - XT-90 - Hard Case



C-49145-X  
Sport Racing 50C - 5400Mah - 4S - 14,8V - XT-90 - Hard Case



C-49146-X  
Sport Racing 50C - 6700Mah - 4S - 14,8V - XT-90 - Hard Case



M1.0 Pinion - Hardened Steel - Shaft Diameter 5mm

- C-72711 • 11 Teeth
- C-72712 • 12 Teeth
- C-72713 • 13 Teeth
- C-72714 • 14 Teeth
- C-72715 • 15 Teeth



C-52005  
Digital Servo - CS-5245 - High Voltage - Coreless Motor - Steel Gear - 45 Kg Torque

## TROUBLESHOOTING - DEPANNAGE - FEHLERSUCHE - PROBLEEMOPLOSSING




**If you have any problems, consult the troubleshooting guide.**

En cas de problème, consultez le guide de dépannage.

Falls Probleme auftreten, schlagen Sie in der Anleitung zur Fehlerbehebung nach.


Raadpleeg de gids voor probleemoplossing als u problemen ondervindt.






**HEX SOCKET HEAD SCREWS**  
DIN 912 - STEEL - 10 PCS

| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3001-16-06 | M1.6         | 6         |
| C-3001-20-04 | M2           | 4         |
| C-3001-20-06 | M2           | 6         |
| C-3001-20-08 | M2           | 8         |
| C-3001-20-10 | M2           | 10        |
| C-3001-20-12 | M2           | 12        |
| C-3001-20-16 | M2           | 16        |
| C-3001-25-06 | M2.5         | 6         |
| C-3001-25-08 | M2.5         | 8         |
| C-3001-25-10 | M2.5         | 10        |
| C-3001-25-12 | M2.5         | 12        |
| C-3001-25-16 | M2.5         | 16        |
| C-3001-25-20 | M2.5         | 20        |
| C-3001-30-06 | M3           | 6         |
| C-3001-30-08 | M3           | 8         |
| C-3001-30-10 | M3           | 10        |
| C-3001-30-12 | M3           | 12        |
| C-3001-30-14 | M3           | 14        |
| C-3001-30-16 | M3           | 16        |
| C-3001-30-20 | M3           | 20        |
| C-3001-30-25 | M3           | 25        |
| C-3001-30-30 | M3           | 30        |
| C-3001-40-06 | M4           | 6         |
| C-3001-40-08 | M4           | 8         |
| C-3001-40-10 | M4           | 10        |
| C-3001-40-12 | M4           | 12        |
| C-3001-40-14 | M4           | 14        |
| C-3001-40-16 | M4           | 16        |
| C-3001-40-18 | M4           | 18        |
| C-3001-40-20 | M4           | 20        |
| C-3001-40-22 | M4           | 22        |




**HEX BUTTON HEAD SCREWS**  
DIN 7380 - STEEL - 10 PCS

| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3003-25-04 | M2.5         | 4         |
| C-3003-25-06 | M2.5         | 6         |
| C-3003-25-08 | M2.5         | 8         |
| C-3003-25-18 | M2.5         | 18        |
| C-3003-30-06 | M3           | 6         |
| C-3003-30-08 | M3           | 8         |
| C-3003-30-10 | M3           | 10        |
| C-3003-30-12 | M3           | 12        |
| C-3003-30-14 | M3           | 14        |
| C-3003-30-16 | M3           | 16        |
| C-3003-30-18 | M3           | 18        |
| C-3003-30-20 | M3           | 20        |
| C-3003-30-23 | M3           | 23        |
| C-3003-30-25 | M3           | 25        |
| C-3003-30-28 | M3           | 28        |
| C-3003-30-30 | M3           | 30        |
| C-3003-30-35 | M3           | 35        |
| C-3003-30-40 | M3           | 40        |
| C-3003-40-06 | M4           | 6         |
| C-3003-40-08 | M4           | 8         |
| C-3003-40-10 | M4           | 10        |
| C-3003-40-12 | M4           | 12        |
| C-3003-40-16 | M4           | 16        |
| C-3003-40-20 | M4           | 20        |
| C-3003-40-25 | M4           | 25        |




**HEX BUTTON HEAD SCREWS**  
TITANIUM - 10 PCS

| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3023-30-06 | M3           | 6         |
| C-3023-30-08 | M3           | 8         |
| C-3023-30-10 | M3           | 10        |
| C-3023-30-12 | M3           | 12        |
| C-3023-30-16 | M3           | 16        |
| C-3023-30-20 | M3           | 20        |
| C-3023-30-25 | M3           | 25        |
| C-3023-40-06 | M4           | 6         |
| C-3023-40-08 | M4           | 8         |
| C-3023-40-10 | M4           | 10        |
| C-3023-40-12 | M4           | 12        |
| C-3023-40-16 | M4           | 16        |
| C-3023-40-20 | M4           | 20        |
| C-3023-40-25 | M4           | 25        |




**HEX FLAT HEAD SCREWS**  
DIN 7991 - STEEL - 10 PCS

| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3002-25-08 | M2.5         | 8         |
| C-3002-30-06 | M3           | 6         |
| C-3002-30-08 | M3           | 8         |
| C-3002-30-10 | M3           | 10        |
| C-3002-30-12 | M3           | 12        |
| C-3002-30-14 | M3           | 14        |
| C-3002-30-15 | M3           | 15        |
| C-3002-30-16 | M3           | 16        |
| C-3002-30-18 | M3           | 18        |
| C-3002-30-20 | M3           | 20        |
| C-3002-40-06 | M4           | 6         |
| C-3002-40-08 | M4           | 8         |
| C-3002-40-10 | M4           | 10        |
| C-3002-40-12 | M4           | 12        |
| C-3002-40-14 | M4           | 14        |
| C-3002-40-16 | M4           | 16        |
| C-3002-40-18 | M4           | 18        |
| C-3002-40-20 | M4           | 20        |
| C-3002-40-25 | M4           | 25        |



**HEX FLAT HEAD SCREWS**  
TITANIUM - 10 PCS

| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3022-30-06 | M3           | 6         |
| C-3022-30-08 | M3           | 8         |
| C-3022-30-10 | M3           | 10        |
| C-3022-30-12 | M3           | 12        |
| C-3022-30-16 | M3           | 16        |
| C-3022-30-20 | M3           | 20        |
| C-3022-40-08 | M4           | 8         |
| C-3022-40-10 | M4           | 10        |
| C-3022-40-12 | M4           | 12        |
| C-3022-40-16 | M4           | 16        |
| C-3002-40-20 | M4           | 20        |




**HEX SET SCREWS**  
DIN 916 - STEEL - 10 PCS


| REF          | NOMINAL SIZE | LENGTH MM |
|--------------|--------------|-----------|
| C-3004-25-03 | M2.5         | 3         |
| C-3004-30-03 | M3           | 3         |
| C-3004-30-05 | M3           | 5         |
| C-3004-30-08 | M3           | 8         |
| C-3004-30-10 | M3           | 10        |
| C-3004-30-12 | M3           | 12        |
| C-3004-30-20 | M3           | 20        |
| C-3004-40-04 | M4           | 4         |
| C-3004-40-06 | M4           | 6         |
| C-3004-40-08 | M4           | 8         |
| C-3004-40-10 | M4           | 10        |
| C-3004-40-12 | M4           | 12        |
| C-3004-50-05 | M5           | 5         |




## NUTS - ECROUS • MUTTERN • MOEREN




| REF         | NOMINAL SIZE | COLOR  |
|-------------|--------------|--------|
| C-3106-20-0 | M2           | Gold   |
| C-3106-20-1 | M2           | Green  |
| C-3106-20-2 | M2           | Purple |
| C-3106-20-3 | M2           | Gun    |
| C-3106-20-4 | M2           | Blue   |
| C-3106-20-5 | M2           | Red    |
| C-3106-20-6 | M2           | Black  |
| C-3106-30-0 | M3           | Gold   |
| C-3106-30-1 | M3           | Green  |
| C-3106-30-2 | M3           | Purple |
| C-3106-30-3 | M3           | Gun    |
| C-3106-30-4 | M3           | Blue   |
| C-3106-30-5 | M3           | Red    |
| C-3106-30-6 | M3           | Black  |
| C-3106-40-0 | M4           | Gold   |
| C-3106-40-1 | M4           | Green  |
| C-3106-40-2 | M4           | Purple |
| C-3106-40-3 | M4           | Gun    |
| C-3106-40-4 | M4           | Blue   |
| C-3106-40-5 | M4           | Red    |
| C-3106-40-6 | M4           | Black  |
| C-3106-50-0 | M5           | Gold   |
| C-3106-50-1 | M5           | Green  |
| C-3106-50-2 | M5           | Purple |
| C-3106-50-3 | M5           | Gun    |
| C-3106-50-4 | M5           | Blue   |
| C-3106-50-5 | M5           | Red    |
| C-3106-50-6 | M5           | Black  |




| REF         | NOMINAL SIZE | COLOR  |
|-------------|--------------|--------|
| C-3107-30-0 | M3           | Gold   |
| C-3107-30-1 | M3           | Green  |
| C-3107-30-2 | M3           | Purple |
| C-3107-30-3 | M3           | Gun    |
| C-3107-30-4 | M3           | Blue   |
| C-3107-30-5 | M3           | Red    |
| C-3107-30-6 | M3           | Black  |
| C-3107-40-0 | M4           | Gold   |
| C-3107-40-1 | M4           | Green  |
| C-3107-40-2 | M4           | Purple |
| C-3107-40-3 | M4           | Gun    |
| C-3107-40-4 | M4           | Blue   |
| C-3107-40-5 | M4           | Red    |
| C-3107-40-6 | M4           | Black  |
| C-3107-50-0 | M5           | Gold   |
| C-3107-50-1 | M5           | Green  |
| C-3107-50-2 | M5           | Purple |
| C-3107-50-3 | M5           | Gun    |
| C-3107-50-4 | M5           | Blue   |
| C-3107-50-5 | M5           | Red    |
| C-3107-50-6 | M5           | Black  |



| REF         | NOMINAL SIZE | COLOR  |
|-------------|--------------|--------|
| C-3101-20-6 | M2           | Black  |
| C-3101-25   | M2.5         | Silver |
| C-3101-25-6 | M2.5         | Black  |
| C-3101-30   | M3           | Silver |
| C-3101-30-6 | M3           | Black  |
| C-3101-40   | M4           | Silver |
| C-3101-40-6 | M4           | Black  |




| REF       | NOMINAL SIZE | COLOR  |
|-----------|--------------|--------|
| C-3104-40 | M4           | Silver |
| C-3104-50 | M5           | Silver |




| REF         | NOMINAL SIZE | COLOR |
|-------------|--------------|-------|
| C-3103-20-6 | M2           | Black |
| C-3103-25-6 | M2.5         | Black |
| C-3103-30-6 | M3           | Black |
| C-3103-40-6 | M4           | Black |
| C-3103-50-6 | M5           | Black |

## BALL BEARINGS




| REF               | ID MM | OD MM | TH MM |
|-------------------|-------|-------|-------|
| C-3611-3-05-08-03 | 5     | 8     | 3     |
| C-3611-3-05-10-04 | 5     | 10    | 4     |
| C-3611-3-06-10-03 | 6     | 10    | 3     |
| C-3611-3-08-16-05 | 8     | 16    | 5     |
| C-3611-3-10-15-04 | 10    | 15    | 4     |
| C-3611-3-12-21-05 | 12    | 21    | 5     |

## SHIMS




| REF             | ID MM | OD MM | TH MM |
|-----------------|-------|-------|-------|
| C-3301-04-06-01 | 4     | 6     | 0.1   |
| C-3301-06-08-01 | 6     | 8     | 0.1   |
| C-3301-08-10-01 | 8     | 10    | 0.1   |
| C-3301-13-16-01 | 13    | 16    | 0.1   |

## STEELWASHERS




| REF       | ID MM | OD MM | TH MM |
|-----------|-------|-------|-------|
| C-3201-30 | 3.2   | 7     | 0.5   |
| C-3201-40 | 4.3   | 9     | 0.8   |
| C-3201-60 | 6.4   | 12    | 1.6   |

## ALUMINIUM WASHERS





WASHER FOR SOCKET HEAD SCREW  
ALUMINIUM - 10 PCS

| REF         | FOR S/H SCREW | ID MM | OD MM | COLOR  |
|-------------|---------------|-------|-------|--------|
| C-3214-20-0 | M2            | 2.2   | 6     | Gold   |
| C-3214-20-1 | M2            | 2.2   | 6     | Green  |
| C-3214-20-2 | M2            | 2.2   | 6     | Purple |
| C-3214-20-3 | M2            | 2.2   | 6     | Gun    |
| C-3214-20-4 | M2            | 2.2   | 6     | Blue   |
| C-3214-20-5 | M2            | 2.2   | 6     | Red    |
| C-3214-20-6 | M2            | 2.2   | 6     | Black  |
| C-3214-25-0 | M2.5          | 2.7   | 7     | Gold   |
| C-3214-25-1 | M2.5          | 2.7   | 7     | Green  |
| C-3214-25-2 | M2.5          | 2.7   | 7     | Purple |
| C-3214-25-3 | M2.5          | 2.7   | 7     | Gun    |
| C-3214-25-4 | M2.5          | 2.7   | 7     | Blue   |
| C-3214-25-5 | M2.5          | 2.7   | 7     | Red    |
| C-3214-25-6 | M2.5          | 2.7   | 7     | Black  |
| C-3214-30-0 | M3            | 3.2   | 8     | Gold   |
| C-3214-30-1 | M3            | 3.2   | 8     | Green  |
| C-3214-30-2 | M3            | 3.2   | 8     | Purple |
| C-3214-30-3 | M3            | 3.2   | 8     | Gun    |
| C-3214-30-4 | M3            | 3.2   | 8     | Blue   |
| C-3214-30-5 | M3            | 3.2   | 8     | Red    |
| C-3214-30-6 | M3            | 3.2   | 8     | Black  |
| C-3214-40-0 | M4            | 4.3   | 10    | Gold   |
| C-3214-40-1 | M4            | 4.3   | 10    | Green  |
| C-3214-40-2 | M4            | 4.3   | 10    | Purple |
| C-3214-40-3 | M4            | 4.3   | 10    | Gun    |
| C-3214-40-4 | M4            | 4.3   | 10    | Blue   |
| C-3214-40-5 | M4            | 4.3   | 10    | Red    |
| C-3214-40-6 | M4            | 4.3   | 10    | Black  |
| C-3214-50-0 | M5            | 5.3   | 10    | Gold   |
| C-3214-50-1 | M5            | 5.3   | 10    | Green  |
| C-3214-50-2 | M5            | 5.3   | 10    | Purple |
| C-3214-50-3 | M5            | 5.3   | 10    | Gun    |
| C-3214-50-4 | M5            | 5.3   | 10    | Blue   |
| C-3214-50-5 | M5            | 5.3   | 10    | Red    |
| C-3214-50-6 | M5            | 5.3   | 10    | Black  |





WASHER FOR BUTTON HEAD SCREW  
ALUMINIUM - 10 PCS

| REF         | FOR B/H SCREW | ID MM | OD MM | COLOR  |
|-------------|---------------|-------|-------|--------|
| C-3211-30-0 | M3            | 3.2   | 10    | Gold   |
| C-3211-30-1 | M3            | 3.2   | 10    | Green  |
| C-3211-30-2 | M3            | 3.2   | 10    | Purple |
| C-3211-30-3 | M3            | 3.2   | 10    | Gun    |
| C-3211-30-4 | M3            | 3.2   | 10    | Blue   |
| C-3211-30-5 | M3            | 3.2   | 10    | Red    |
| C-3211-30-6 | M3            | 3.2   | 10    | Black  |
| C-3211-40-0 | M4            | 4.3   | 12    | Gold   |
| C-3211-40-1 | M4            | 4.3   | 12    | Green  |
| C-3211-40-2 | M4            | 4.3   | 12    | Purple |
| C-3211-40-3 | M4            | 4.3   | 12    | Gun    |
| C-3211-40-4 | M4            | 4.3   | 12    | Blue   |
| C-3211-40-5 | M4            | 4.3   | 12    | Red    |
| C-3211-40-6 | M4            | 4.3   | 12    | Black  |



WASHER FOR BUTTON HEAD SCREW  
ALUMINIUM - 10 PCS

| REF         | FOR B/H SCREW | ID MM | OD MM | COLOR  |
|-------------|---------------|-------|-------|--------|
| C-3212-30-0 | M3            | 3.2   | 15    | Gold   |
| C-3212-30-1 | M3            | 3.2   | 15    | Green  |
| C-3212-30-2 | M3            | 3.2   | 15    | Purple |
| C-3212-30-3 | M3            | 3.2   | 15    | Gun    |
| C-3212-30-4 | M3            | 3.2   | 15    | Blue   |
| C-3212-30-5 | M3            | 3.2   | 15    | Red    |
| C-3212-30-6 | M3            | 3.2   | 15    | Black  |



WASHER FOR FLAT HEAD SCREW  
ALUMINIUM - 10 PCS

| REF         | FOR F/H SCREW | ID MM | OD MM | COLOR  |
|-------------|---------------|-------|-------|--------|
| C-3213-30-0 | M3            | 3.2   | 8     | Gold   |
| C-3213-30-1 | M3            | 3.2   | 8     | Green  |
| C-3213-30-2 | M3            | 3.2   | 8     | Purple |
| C-3213-30-3 | M3            | 3.2   | 8     | Gun    |
| C-3213-30-4 | M3            | 3.2   | 8     | Blue   |
| C-3213-30-5 | M3            | 3.2   | 8     | Red    |
| C-3213-30-6 | M3            | 3.2   | 8     | Black  |
| C-3213-40-0 | M4            | 4.3   | 10    | Gold   |
| C-3213-40-1 | M4            | 4.3   | 10    | Green  |
| C-3213-40-2 | M4            | 4.3   | 10    | Purple |
| C-3213-40-3 | M4            | 4.3   | 10    | Gun    |
| C-3213-40-4 | M4            | 4.3   | 10    | Blue   |
| C-3213-40-5 | M4            | 4.3   | 10    | Red    |
| C-3213-40-6 | M4            | 4.3   | 10    | Black  |
| C-3213-50-0 | M5            | 5.3   | 12    | Gold   |
| C-3213-50-1 | M5            | 5.3   | 12    | Green  |
| C-3213-50-2 | M5            | 5.3   | 12    | Purple |
| C-3213-50-3 | M5            | 5.3   | 12    | Gun    |
| C-3213-50-4 | M5            | 5.3   | 12    | Blue   |
| C-3213-50-5 | M5            | 5.3   | 12    | Red    |
| C-3213-50-6 | M5            | 5.3   | 12    | Black  |

## WARRANTY ( All models )



If material defects or manufacturing faults should arise in a product distributed or manufactured by Team Corally / JSP Group Intl bvba, and purchased by a consumer, we Team Corally / JSP Group Intl bvba acknowledge the obligation to correct those faults or defects within the limitations described below. This manufacturers warranty is in addition to, and does not affect, the legal or contractual rights of the consumer which arise from the purchase of such products. Team Corally / JSP Group Intl bvba guarantees the consumer that its products are free from material, manufacturing, and construction faults, as determined by the general state of knowledge and technology valid at the time of manufacturing. The fault responsible for causing the damage must be proven to have been present in the product at this time. Claims for compensation arising from consequential damage or product liability will not be considered valid unless they fall under peremptory provisions of the law. If material defects or manufacturing faults should arise in a product distributed or manufactured by Team Corally / JSP Group Intl bvba in the European community (EC) and purchased by a consumer, then Team Corally / JSP Group Intl bvba undertakes to correct those defects within the limitations described below. This manufacturer's declaration does not affect the consumer's legal or contractual rights regarding defects arising from the purchase contract between the consumer and the dealer or reseller. **Extend of the Warranty**

If a claim is made under warranty, we take at our discretion to repair or replace the defective goods. We will not consider supplementary claims, especially for reimbursement of costs relating to the defect (e.g. installation / removal costs) and compensation for consequent damages unless they are allowed by statute. This does not affect claims on legal regulations, especially according to the product liability law.

### Provisions of the Warranty

The purchaser is required to make the warranty claim in writing, and must enclose original proof of purchase (e.g. invoice, receipt, delivery note) and the appropriate warranty card. He must send the defective goods to our local representatives or directly to Team Corally / JSP Group Intl bvba, Geelseweg 80, 2250 Olen, Belgium at his own risk and cost.

The purchaser should state the material defect or manufacturing fault, or symptoms of the fault, as accurate as possible, so that we can check if our warranty obligation is applicable. The goods are transported from the consumer to us, and from us to the consumer, entirely at the risk and cost of the consumer.

### Invalidation of the Warranty

The consumer cannot make a claim under warranty when the fault is affecting the use of the product arising from natural wear, competition use, or improper use (including installation) or external forces. The consumer's adherence to the building and operating instructions relevant to the model, including the installation, operation, use of, and maintenance of, model-related components cannot be supervised by Team Corally / JSP Group Intl bvba. Therefore Team Corally / JSP Group Intl bvba is in no way liable for loss, damage, or costs resulting from improper use, or behaviour in any way connected to the above described provisions. Unless otherwise required by law, Team Corally / JSP Group Intl bvba is in no way whatever liable to provide compensation for damages arising from the improper use of the model (including personal injury, death, damage to buildings, loss of turnover, loss of business, or interruption of business, or any other direct, or indirectly caused, consequential damage).

### Duration of Validity

The claim period is 24 months from the date of purchase of the product by the consumer from a dealer in the European Community (EC) counted from the date of purchase. The claim period is 12 months from the date of purchase of the product by the consumer from a dealer outside the European Community (EC) counted from the date of purchase. If a defect arises after the end of the claim period, or if evidence or documents required according to this declaration in order to make the claim valid are not presented until after this period, then the consumer forfeits any rights or claims from this declaration. The guarantee period is not prolonged by the granting of any claims within the framework of this warranty, especially in the case of repair or replacement. The guarantee period also does not restart in such cases.

### Warranty Expiration

If we do not acknowledge the validity of a claim based on this declaration within the claim period, all claims based on this declaration will expire after six months from the time of registering the claim; however this cannot occur prior to the end of the claim period.

For any support, contact us at [support.corally.com](http://support.corally.com)

## DECLARATION OF CONFORMITY

### EU-Konformitätserklärung/ Déclaration de Conformité UE

(in accordance with ISO/IEC 17050-1) / (in Übereinstimmung mit ISO/IEC 17050-1) /  
(Conformément à la norme ISO/IEC 17050-1)

Description : **SHIROI XP 6S - SHORT COURSE 4WD - 1/8 - RTR**  
Item Number: **C-00278**

This declaration is issued under the sole responsibility of the manufacturer.  
Die alleinige Verantwortung für die Ausstellung dieser Erklärung trägt der Hersteller.  
La présente déclaration est établie sous la seule responsabilité du fabricant.

Product(s)/Produkt(e)/ Produit(s) : **SHIROI XP 6S - SHORT COURSE 4WD - 1/8 - RTR**

The object of declaration described above is in conformity with the relevant Union harmonization Legislation, specifically the requirements of the specifications listed below, following the provisions of the European RED Directive 2014/53/EU:  
Der Gegenstand dieser Erklärung ist konform mit den Harmonisierungsrechtsvorschriften der Europäischen Union, insbesondere mit den unten aufgeführten Bestimmungen, und folgt der europäischen RED Direktive 2014/53/EU:  
L'objet de la déclaration décrit ci-dessus est conforme à la législation pertinente en matière d'harmonisation de l'Union européenne, en particulier les exigences des spécifications énumérées ci-dessous, conformément aux dispositions des directives européennes RED 2014/53/EU:

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| EN 300 440 V2.1.1:2017   | EN 301 489-3 V1.6.1:2013                          |
| EN 301 489-1 V2.1.1:2017 | EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013 |
| EN 62479:2010            | EN 55024:2010+A1:2015                             |
| EN 55032:2015            | EN 61000-3-3:2013                                 |
| EN 61000-3-2:2014        |                                                   |

JSP GROUP INTL • Geelseweg, 80 • 2250 Olen • Belgium

Signed for and on behalf of/ Unterzeichnet für und im Namen von/ Signé pour et au nom de :

Place/Ort/Lieu and Date/Datum/Data : **Olen, Belgium, 3 Juni 2025**

Name/Nom: **Stefan Engelen**  
Title/Titel/Titre : **Ceo**

Signature/Unterschrift :




**FEDERAL COMMUNICATIONS COMMISSION**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE JSP GROUP INTL BVBA / CORALLY, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| FCC IDENTIFIER :        | 2ASFS-C59060                                       |
| Name of Grantee :       | JSP GROUP INTL BVBA / CORALLY                      |
| Equipment Class :       | Part 15 Low Power Communication Device Transmitter |
| Notes :                 | Corally CT2R - C-59060                             |
| FCC Rules :             | 15C                                                |
| Frequency Range (MHZ) : | 2410.0 - 2480.0                                    |





**WWW.CORALLY.COM**

**Team Corally is a registered trademark licensed to  
JSP Group Intl bvba • Geelseweg 80 • B-2250 OLEN • Belgium  
Tel: +32 14 25 92 94 • Info@corally.com**